

Overview

HPE Alletra Storage Server 4120

Are you looking for server-based data infrastructure with an optimal balance of performance and economic capacity for data-driven initiatives?

The HPE Alletra Storage Server 4120 is specifically designed to run the broadest range of data storage-intensive workloads to power your data-driven initiatives to success. From analytics data lakes and general purpose file and object Software-Defined Storage to active archives, converged data protection, and so much more, it delivers the capabilities you need at ideal economics with trusted security and a cloud operating experience. This includes the option to consume as-a-service via HPE GreenLake enabling you to shift from owning and maintaining to simply utilizing it. HPE Alletra Storage Server 4000 systems provide the data infrastructure for any successful data driven organization.



HPE Alletra Storage Server 4120 (24LFF SKU shown)

Overview




HPE Alletra Storage Server 4120 Configure-to-order System Front View (24LFF SKU shown)

- | | |
|---|---------------------------------|
| 1. Health LED | 5. USB 3.0 port |
| 2. Power On/Standby button and system power LED | 6. UID button/LED |
| 3. iLO Service Port | 7. Drive cage 1 release latches |
| 4. NIC status LED | |




Overview



HPE Alletra Storage Server 4120 Configure-to-order System Internal View

- | | |
|--|-----------------------------|
| 1. Drive Cage 1 | 10. Primary riser connector |
| 2. Drive Cage 2 | 11. VBU connector (OCP1) |
| 3. Up to 2 processors (2 processors installed with standard heat sink shown) | 12. OCP1 connector |
| 4. DDR5 DIMM slots (Fully populated 24 DIMMs shown) | 13. PCIe Gen3 connector |
| 5. Secondary riser connector | 14. MCIO connectors |
| 6. System maintenance switch | 15. System battery |
| 7. OCP2 connectors | 16. MCIO 1A connector |
| 8. Serial port connector | 17. System fans |
| 9. Internal USB connector | |

Overview



HPE Alletra Storage Server 4120 Configure-to-order System Rear View

- | | |
|--|---------------------------|
| 1. Primary riser or drive cage 4 (riser shown) | 7. OCP NIC 3.0 slot 2 |
| 2. Secondary riser or drive cage 5 (riser shown) | 8. Serial port (optional) |
| 3. Tertiary riser | 9. iLO management port |
| 4. Power supply LED (bay 1 & 2) | 10. USB 3.0 ports |
| 5. Flex Slot power supply bay 1 & 2 | 11. UID LED |
| 6. Video port | 12. OCP NIC 3.0 slot 1 |



Overview

What's New

- Successor to the industry leading HPE Apollo 4200 Gen10 server. Complement to the differentiated HPE Apollo 4200 Gen10 Plus server.
- More data throughput with up to 109%¹ more bandwidth, double the now PCIe Gen5 NVMe SSDs for cache and metadata, and up to four new generation tri-mode storage controllers.
- More data processing with latest 4th generation Intel® Xeon® Scalable processors delivering more performance plus DDR5 memory with up to 75%² more bandwidth.
- Enhanced zero trust security from silicon to software and factory to cloud with HPE Integrated Lights Out 6, including new support for the DMTF Security Protection Data Model.
- HPE Greenlake for Compute Ops Management offers cloud-native control and operations for simplified and automated lifecycle management, including dramatically easier firmware management.
- New 5th Generation Intel® Xeon® Scalable Processors support
- New HPE DDR5 SmartMemory options – Registered (RDIMM), 5600MT/s support
- NVIDIA L4 and A2 GPU accelerators support
- New HPE NVMe EDSFF E3.s 1T MU and RI SSD SKUs support

Notes:

- ¹ Based on 24 LFF and 12 EDSFF configuration comparing to HPE Apollo 4200 Gen10 Plus.
- ² 5600 MT/s versus 3200 MT/s for the 3rd generation Intel® Xeon® Scalable processors.

Platform Information

Form Factor

- 2U rack

Chassis Types

- 24 LFF SAS 24Gb/SATA 6Gb
- 48 SFF SAS 24Gb/SATA 6Gb

Notes:

- Optional Rear Drive Cages:
 - o 2 or 2 + 2 LFF SAS 12Gb/SATA 6Gb Drive Cages (only for 24LFF chassis),
 - o 6 SFF SAS 24Gb/SATA 6Gb/NVMe U.3 x4 Tri-mode Drive Cage
 - o 12 EDSFF E3S EC1 EDSFF NVMe x5 Drive Cage

System Fans

- 5 system dual-fan modules shipped as standard
-



Standard Features

Processors

Up to 2 of the following depending on model.

Notes:

- The 2nd digit of the processor model number “x4xx” is used to denote the processor generation (i.e. 4 = 4th generation)
- This table covers the public Intel offering only.
- For more information regarding Intel Xeon processors, please see the following <http://www.intel.com/xeon>.

Platinum Processors							
Intel Xeon Models	CPU Frequency	Cores	L3 Cache	Power	UPI	DDR5	SGX Enclave size
Platinum 9468 Processor	2.1 GHz	48	105 MB	350 W	4 @ 16 GT/s	4800 MT/s	512GB
Platinum 9462 Processor	2.7 GHz	32	75 MB	350 W	3 @ 16 GT/s	4800 MT/s	128GB
Platinum 9460 Processor	2.2 GHz	40	97.5 MB	350 W	3 @ 16 GT/s	4800 MT/s	128GB
Platinum 8568Y+ Processor	2.3 GHz	48	300 MB	350 W	4 @ 20 GT/s	5600 MT/s	512GB
Platinum 8562Y+ Processor	2.8 GHz	32	60 MB	300 W	3 @ 20 GT/s	5600 MT/s	512GB
Platinum 8558 Processor	2.1 GHz	48	260 MB	330 W	4 @ 20 GT/s	5200 MT/s	512GB
Platinum 8468 Processor	2.1 GHz	48	105 MB	350 W	4 @ 16 GT/s	4800 MT/s	512GB
Platinum 8462+ Processor	2.8 GHz	32	60 MB	300 W	3 @ 16 GT/s	4800 MT/s	128GB
Platinum 8460Y+ Processor	2.0 GHz	40	105 MB	300 W	4 @ 16 GT/s	4800 MT/s	128GB
Platinum 8452Y Processor	2.0 GHz	36	67.5 MB	300 W	4 @ 16 GT/s	4800 MT/s	128GB

Notes:

- 2 socket capable, 2S – 4 or 3 UPI @ 20 or 16 GT/s.
- 4th and 5th Generation: 8-Channel DDR5 1DPC @ 5600 - 4800 MT/s.
- 80 lanes PCIe 5.0, advanced RAS.
- Y Supports Intel Speed Select Technology – Performance Profile 2.0 (Intel SST-PP).
- +: Feature Plus: Support AMX, DLB, DSA, IAA and QAT additionally

Gold Processors							
Intel Xeon Models	CPU Frequency	Cores	L3 Cache	Power	UPI	DDR5	SGX Enclave size
Gold 6554S Processor	2.2 GHz	36	180 MB	270 W	3 @ 20 GT/s	5200 MT/s	128GB
Gold 6548Y+ Processor	2.5 GHz	32	60 MB	250 W	3 @ 20 GT/s	5200 MT/s	128GB
Gold 6544Y Processor	3.6 GHz	16	45 MB	270 W	3 @ 20 GT/s	5200 MT/s	128GB
Gold 6542Y Processor	2.9 GHz	24	60 MB	250 W	3 @ 20 GT/s	5200 MT/s	128GB
Gold 6538Y+ Processor	2.2 GHz	32	60 MB	225 W	3 @ 20 GT/s	5200 MT/s	128GB
Gold 6538N Processor	2.1 GHz	32	60 MB	205 W	3 @ 20 GT/s	5200 MT/s	128GB
Gold 6534 Processor	3.9 GHz	8	22.5 MB	195 W	3 @ 20 GT/s	4800 MT/s	128GB
Gold 6530 Processor	2.1 GHz	32	160 MB	270 W	3 @ 20 GT/s	4800 MT/s	128GB
Gold 6526 Processor	2.8 GHz	16	37.5 MB	195 W	3 @ 20 GT/s	5200 MT/s	128GB
Gold 6454S Processor	2.2 GHz	32	60 MB	270 W	4 @ 16 GT/s	4800 MT/s	128GB
Gold 6448Y Processor	2.1 GHz	32	60 MB	225 W	3 @ 16 GT/s	4800 MT/s	128GB
Gold 6444Y Processor	3.6 GHz	16	45 MB	270 W	3 @ 16 GT/s	4800 MT/s	128GB
Gold 6442Y Processor	2.6 GHz	24	60 MB	225 W	3 @ 16 GT/s	4800 MT/s	128GB
Gold 6438Y+ Processor	2.0 GHz	32	60 MB	205 W	3 @ 16 GT/s	4800 MT/s	128GB
Gold 6434 Processor	3.7 GHz	8	22.5 MB	195 W	3 @ 16 GT/s	4800 MT/s	128GB
Gold 6430 Processor	2.1 GHz	32	60 MB	270 W	3 @ 16 GT/s	4400 MT/s	128GB
Gold 6426Y Processor	2.5 GHz	16	37.5 MB	185 W	3 @ 16 GT/s	4800 MT/s	128GB



Standard Features

Intel Xeon Models	CPU Frequency	Cores	L3 Cache	Power	UPI	DDR5	SGX Enclave size
Gold 6414U Processor	2.0 GHz	32	60 MB	250 W	N/A	4800 MT/s	512GB
Gold 5520+ Processor	2.2 GHz	28	52.5 MB	205 W	3 @ 20 GT/s	4800 MT/s	128GB
Gold 5515+ Processor	3.2 GHz	8	22.5 MB	165 W	3 @ 20 GT/s	4800 MT/s	128GB
Gold 5512U Processor	2.1 GHz	28	52.5 MB	185 W	N/A	4800 MT/s	128GB
Gold 5420+ Processor	2.0 GHz	28	52.5 MB	205 W	3 @ 16 GT/s	4400 MT/s	128GB
Gold 5418Y Processor	2.0 GHz	24	45 MB	185 W	3 @ 16 GT/s	4400 MT/s	128GB
Gold 5418N Processor	1.8 GHz	24	45 MB	165 W	3 @ 16 GT/s	4000 MT/s	128GB
Gold 5416S Processor	2.0 GHz	16	30 MB	150 W	3 @ 16 GT/s	4400 MT/s	128GB
Gold 5415+ Processor	2.9 GHz	8	22.5 MB	150 W	3 @ 16 GT/s	4400 MT/s	128Gb
Gold 5412U Processor	2.1 GHz	24	45 MB	185 W	N/A	4400 MT/s	128GB

Notes:

- 2 socket capable, 2S - 4 or 3 UPI @ 20 or 16 GT/s, except U SKUs
- 4th and 5th Generation: 8-Channel DDR5 1DPC @ 5200 - 4000 MT/s.
- 80 lanes PCIe 5.0, advanced RAS.
- Y Supports Intel Speed Select Technology – Performance Profile 2.0 (Intel SST-PP).
- U Supported in one-socket configurations only.
- S SKUs are storage & hyperconverged infrastructure (HCI) optimized SKUs
- +: Feature Plus: Support AMX, DLB, DSA, IAA and QAT additionally

Silver Processors							
Intel Xeon Models	CPU Frequency	Cores	L3 Cache	Power	UPI	DDR5	SGX Enclave size
Silver 4516Y+ Processor	2.2 GHz	24	45 MB	185 W	2 @ 16 GT/s	4400 MT/s	64GB
Silver 4514Y Processor	2.0 GHz	16	30 MB	150 W	2 @ 16 GT/s	4400 MT/s	64GB
Silver 4510 Processor	2.4 GHz	12	30 MB	150 W	2 @ 16 GT/s	4400 MT/s	64GB
Silver 4509Y Processor	2.6 GHz	8	22.5 MB	125 W	2 @ 16 GT/s	4400 MT/s	64GB
Silver 4416+ Processor	2.0 GHz	20	37.5 MB	165 W	2 @ 16 GT/s	4000 MT/s	64GB
Silver 4410Y Processor	2.0 GHz	12	30 MB	150 W	2 @ 16 GT/s	4000 MT/s	64Gb

Notes:

- 2 socket capable, 2S - 2 UPI @ 16 GT/s, except U SKUs
- 4th and 5th Generation: 8-Channel DDR5 1DPC @ 4400 - 4000 MT/s
- 80 lanes PCIe 5.0, advanced RAS.
- Y Supports Intel Speed Select Technology – Performance Profile 2.0 (Intel SST-PP).
- +: Feature Plus: Support AMX, DLB, DSA, IAA and QAT additionally

Bronze Processors							
Intel Xeon Models	CPU Frequency	Cores	L3 Cache	Power	UPI	DDR5	SGX Enclave size
Bronze 3508U Processor	2.1 GHz	8	22.5 MB	125 W	N/A	4400 MT/s	64GB
Bronze 3408U Processor	1.8 GHz	8	22.5 MB	125 W	N/A	4000 MT/s	64GB

Notes:

- 4th and 5th Generation: 8-Channel DDR5 1DPC @ 4400 - 4000 MT/s
- 80 lanes PCIe 5.0, advanced RAS, except Bronze 3508U Processor.
- U Supported in one-socket configurations only.
- Bronze 3508U Processor only supports PCIe Gen4



Standard Features

Chipset

Intel C741 Chipset

Notes: For more information regarding Intel® chipsets, please see the following URL:

<http://www.intel.com/products/server/chipsets/>.

On System Management Chipset

HPE iLO 6 ASIC

Notes: Read and learn more in the [iLO QuickSpecs](#).

Memory

Type	HPE DDR5 Smart Memory Registered (RDIMM)
DIMM Slots Available	24 12 DIMM slots per processor, 8 channels per processor, 2-2-1-1 deployment
Maximum capacity (RDIMM)	4 TB 16 x 256 GB RDIMM @ 4800 MT/s 3TB 24 x 128 GB RDIMM @ 5600 MT/s

Notes:

- The maximum memory speed is limited by the processor selection.
- The maximum capacity per system is limited by the overall configuration selection due to thermal capacity. Contact HPE representative for 6TB configuration details.

Memory Protection

Advanced ECC

Advanced ECC uses single device data correction to detect and correct single and all multibit error that occurs within a single DRAM chip.

Expansion Slots

Primary Riser

Notes: Bus width indicates the number of physical electrical lanes running to the connector.

PCIe Primary Riser Kit

Slot#	Techonology	Bus Width	Connector Width	Slot Form Factor	Notes
1	PCIe 5.0	X16	X16	Full-height,half-length slot	Proc1
2	PCIe 5.0	X16	X16	Full-height,half-length slot	Proc1
3	PCIe 5.0	X16	X16	Full-height,half-length slot	Proc1

Secondary Riser

Notes:

- Bus width indicates the number of physical electrical lanes running to the connector.
- When 4th UPI enabled, Slot 4 is running PCIe 4.0 performance. The 4th UPI is disabled by default.



Standard Features

PCIe Secondary Riser Kit

Slot#	Technology	Bus Width	Connector Width	Slot Form Factor	Notes
4	PCIe 5.0*	X16	X16	Full-height,half-length slot	Proc2
5	PCIe 5.0	X16	X16	Full-height,half-length slot	Proc2
6	PCIe 5.0	X16	X16	Full-height,half-length slot	Proc2

Primary and Secondary 1U Riser

Notes:

- Bus width indicates the number of physical electrical lanes running to the connector.
- Primary and secondary 1U riser is included in 6SFF x4 Tri-Mode U.3 BC Rear Drive Cage (P51784-B21) and 12EDSFF E3.S 1T x4 Rear Drive Cage (P50875-B21) Upgrade Kit .

PCIe Primary and Secondary 1U Riser Kit

Slot#	Technology	Bus Width	Connector Width	Slot Form Factor	Notes
3	PCIe 5.0	X16	X16	Full-height,half-length slot	Proc1
6	PCIe 5.0	X16	X16	Full-height,half-length slot	Proc2

Tertiary Riser

Notes:

- Tertiary riser is shipped as standard
- Bus width indicates the number of physical electrical lanes running to the connector.
- When 4th UPI enabled, Slot 8 is running PCIe 4.0 performance. The 4th UPI is disabled by default.

PCIe Tertiary Riser

Slot#	Technology	Bus Width	Connector Width	Slot Form Factor	Notes
7	PCIe 5.0	X16	X16	Full-height,half-length slot	Proc2
8	PCIe 5.0*	X16	X16	Full-height,half-length slot	Proc1

Internal Storage Devices

- **Hard Drives**
None ship standard

Storage Controllers

NVMe Boot Devices

- **Optional HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device**

Notes:

- NS204i-u does not occupy a PCIe slot and internal only for Alletra Storage Server 4120.
- 2pcs of 480GB M.2 NVMe SSD are included in the NS204i-u Hot Plug Boot Device
- RAID 1 supported on the NS204i-u Hot Plug Boot Device.

Smart Array Controller

- **HPE Alletra Storage Server 41X0 SR 32-port PCIe FIO Storage Controller**

Notes:

- Only available for factory integrated
- Required 1 or 2 for 24LFF CTO SKU
- Required 2 for 48SFF CTO SKU



Standard Features

- **HPE Alletra Storage Server 41X0 Alletra Storage Server 41X0 MR 16-port PCIe FIO Storage Controller**

Notes:

- Only available for factory integrated
- Only available for 24LFF CTO SKU
- Required 2 for 24LFF CTO SKU

- **HPE SR932i-p Gen11 x32 Lanes 8GB Wide Cache PCI SPDM Plug-in Storage**

Notes: suggested for field upgrade only

- **HPE MR416i-p Gen11 x16 Lanes 8GB Cache PCI SPDM Plug-in Storage Controller**

Notes: suggested for field upgrade only

- **HPE MR216i-p Gen11 x16 Lanes without Cache PCI SPDM Plug-in Storage Controller**

Notes: For additional details, please visit:

- [HPE Compute MR Gen11 Controllers Quick Spec](#)
- [HPE Compute SR Gen11 Controllers Quick Spec](#)

Maximum Internal Storage

Maximum Storage		
Storage	Capacity	Configuration
Standard Cage 1/2 Hot Plug 24LFF SAS HDD	480 TB	24 x 20 TB
Standard Cage 1/2 Hot Plug 24LFF SATA HDD	480 TB	24 x 20 TB
Standard Cage 1/2 Hot Plug 24LFF SAS SSD	184.32 TB	24 x 7.68 TB
Standard Cage 1/2 Hot Plug 24LFF SATA SSD	21.98 TB	24 x 960 GB
Standard Cage 1/2 Hot Plug 48SFF SAS HDD	115.2 TB	48 x 2.4 TB
Standard Cage 1/2 Hot Plug 48SFF SATA HDD	96 TB	48 x 2 TB
Standard Cage 1/2 Hot Plug 48SFF SAS SSD	734.4 TB	48 x 15.36 TB
Standard Cage 1/2 Hot Plug 48SFF SATA SSD	368.64 TB	48 x 7.68 TB
Optional Cage 3 Hot Plug 2LFF SAS HDD	40 TB	2 x 20 TB
Optional Cage 3 Hot Plug 2LFF SATA HDD	40 TB	2 x 20 TB
Optional Cage 3 Hot Plug 2LFF SAS SSD	15.36 TB	2 x 7.68 TB
Optional Cage 3 Hot Plug 2LFF SATA SSD	1.83 TB	2 x 960 GB
Optional Cage 3 Hot Plug 6SFF SAS SSD	92.16 TB	6 x 15.36 TB
Optional Cage 3 Hot Plug 6SFF SATA SSD	46.08 TB	6 x 7.68 TB
Optional Cage 3 Hot Plug 6SFF NVMe SSD	92.16 TB	6 x 15.36 TB
Optional Cage 3 Hot Plug 12EDSFF NVMe SSD	184.32 TB	12 x 15.36 TB
Optional Cage 4 Hot Plug 2LFF SAS HDD	40 TB	2 x 20 TB
Optional Cage 4 Hot Plug 2LFF SATA HDD	40 TB	2 x 20 TB
Optional Cage 4 Hot Plug 2LFF SAS SSD	15.36 TB	2 x 7.68 TB
Optional Cage 4 Hot Plug 2LFF SATA SSD	1.83 TB	2 x 960 GB

Notes:

- SFF NVMe PCIe SSD is only supported in the optional SFF Drive Cage 3
- SFF Drive Cage 3 support SSD only
- Only 1 optional SFF drive cage or 2 optional LFF drive cages can be installed on the rear

Internal Storage Devices

- Hard Drives
- None ship standard.



Standard Features

Graphics

- Integrated video standard
 - Video modes up to 1920 x 1200 @ 60 Hz (32 bpp)
 - 16 MB Video Memory
- HPE iLO 6 on system management memory
 - 32 MB Flash
 - 4 Gbit DDR3 with ECC protection

Power Supply

- HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit
Notes: Available in 94% efficiency.
- HPE 1000W Flex Slot Titanium Hot Plug Low Halogen Power Supply Kit
Notes: Available in 96% efficiency.
- HPE 1600W Flex Slot -48VDC Hot Plug Power Supply Kit
- HPE 1600W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit
Notes:
 - Available in 94% efficiency.
 - 1600W Power supplies only support high line voltage (200 VAC to 240 VAC).
- HPE 1800-2200W Flex Slot Titanium Hot Plug Low Halogen Power Supply Kit
Notes:
 - Available in 96% efficiency.
 - 1800-2200W Power supplies only support high line voltage (200 VAC to 240 VAC).
- HPE 1600W ~48VDC Power Supply Kit

HPE Flexible Slot (Flex Slot) Power Supplies share a common electrical and physical design that allows for hot plug, tool-less installation into HPE ProLiant Gen10 Plus Performance Servers. Flex Slot power supplies are certified for high-efficiency operation and offer multiple power output options, allowing users to "right-size" a power supply for specific server configurations. This flexibility helps to reduce power waste, lower overall energy costs, and avoid "trapped" power capacity in the data center.

All pre-configured servers ship with a standard 6-foot IEC C-13/C-14 jumper cord (A0K02A). This jumper cord is also included with each standard AC power supply option kit. If a different power cord is required, please check the [ProLiant Power Cables](#) web page.

To review the power requirements for your selected system, please use the [HPE Power Advisor Tool](#).

For information on power specifications and technical content visit [HPE Server power supplies](#).

Interfaces

Serial	1 port – Optional, rear
VGA Port	1 port – Standard, rear
Network Ports	None. Choice of OCP or stand up card, supporting a wide range of NIC adapters
HPE iLO Remote Management Network Port	1 GbE Dedicated
Front iLO Service Port	1 standard
USB 3.0	4 standard on all models: 1 front, 2 rear, 1 internal



Standard Features

Operating Systems and Virtualization Software

- [Windows Server 2019](#)
- [Windows Server 2022](#)
- [Red Hat Enterprise Linux \(RHEL\) 8.6](#)
- [Red Hat Enterprise Linux \(RHEL\) 9.0](#)
- [SUSE Linux Enterprise Server \(SLES\) 15 SP4](#)
- [VMware 7.0 U3](#)
- [VMware 8.0](#)
- [Canonical Ubuntu 20.04 and 22.04](#)

Notes: For more information on Hewlett Packard Enterprise Certified and Supported ProLiant Servers for OS and Virtualization Software and latest listing of software drivers available for your server visit: <http://www.hpe.com/info/ossupport>

Industry Standard Compliance

- ACPI 6.4 Compliant
- PCIe 5.0 Compliant
- WOL Support
- Microsoft® Logo certifications
- PXE Support
- USB 3.2 Gen1 Compliant
- SMBIOS 3.4
- Redfish API
- IPMI 2.0
- Secure Digital 4.0
- TPM 2.0 support
- Advanced Encryption Standard (AES)
- Triple Data Encryption Standard (3DES)
- SNMP v3
- TLS 1.2
- DMTF Systems Management Architecture for Server Hardware Command Line (SMASH CLP)
- One Button Secure Erase Enhancements

Notes:

- For additional technical, thermal details regarding ambient temperature, humidity, and feature support, please visit <http://www.hpe.com/servers/ashrae>
- At Standard Operating Support conditions, there is no time limitation for operating the servers in ASHRAE Class A2 conditions, unless otherwise specified in the applicable product information.
- UEFI (Unified Extensible Firmware Interface Forum) 2.7red hat

Embedded Management

HPE Integrated Lights-Out (HPE iLO)

Monitor your servers for ongoing management, service alerting, reporting and remote management with HPE iLO. Learn more at <http://www.hpe.com/info/ilo>.

UEFI

Configure and boot your servers securely with industry standard Unified Extensible Firmware Interface (UEFI). Learn more at <http://www.hpe.com/servers/uefi>.



Standard Features

Intelligent Provisioning

Hassle free server and OS provisioning for one or more servers with Intelligent Provisioning. Learn more at <http://www.hpe.com/servers/intelligentprovisioning>

iLO RESTful API

iLO RESTful API is Redfish API conformance and offers simplified server management automation such as configuration and maintenance tasks based on modern industry standards. Learn more at <http://www.hpe.com/info/restfulapi>.

Server Utilities

Active Health System

The HPE Active Health System (AHS) is an essential component of the iLO management portfolio that provides continuous, proactive health monitoring of HPE servers. Learn more at <http://www.hpe.com/servers/ahs>.

Active Health System Viewer

Use the Active Health System Viewer, a web-based portal, to easily read AHS logs and speed problem resolution with HPE self-repair recommendations, to learn more visit: <http://www.hpe.com/servers/ahsv>.

Smart Update

Keep your servers up to date with the HPE Smart Update solution by using Smart Update Manager (SUM) to optimize the firmware and driver updates of the Service Pack for ProLiant (SPP). Learn more at <https://www.hpe.com/us/en/servers/smart-update.html>

iLO Amplifier Pack

Designed for large enterprise and service provider environments with hundreds of HPE servers, the iLO Amplifier Pack is a free, downloadable open virtual application (OVA) that delivers the power to discover, inventory and update Gen8, Gen9 and Gen10 HPE servers at unmatched speed and scale. Use with an iLO Advanced License to unlock full capabilities. Learn more at <http://www.hpe.com/servers/iLOamplifierpack>.

HPE iLO Mobile Application

Enables the ability to access, deploy, and manage your server anytime from anywhere from select smartphones and mobile devices. For additional information please visit: <http://www.hpe.com/info/ilo/mobileapp>.

RESTful Interface Tool

RESTful Interface tool (iLOREST) is a single scripting tool to provision using iLO RESTful API to discover and deploy servers at scale. Learn more at <http://www.hpe.com/info/resttool>.

Scripting Tools

Provision one to many servers using your own scripts to discover and deploy with Scripting Tool (STK) for Windows and Linux or Scripting Tools for Windows PowerShell. Learn more at <http://www.hpe.com/servers/powershell>.

HPE OneView Standard

HPE OneView Standard can be used for inventory, health monitoring, alerting, and reporting without additional fees. It can monitor multiple HPE server generations. The user interface is similar to the HPE OneView Advanced version, but the software-defined functionality is not available. Learn more at <http://www.hpe.com/info/oneview>.



Standard Features

HPE GreenLake for Compute Ops Management

HPE is intelligently transforming compute management with a completely new as a service experience that delivers greater security, simplicity, and efficiency. Discover a completely modernized compute management experience delivered through HPE GreenLake that securely streamlines operations from edge-to-cloud, and automates key lifecycle tasks (onboard, update, manage and monitor HPE servers), bringing the agility and greater efficiencies to wherever compute devices reside via a unified single browser-based interface.

Compute Ops Management is built on a unique cloud-native architecture that abstracts, manages and controls HPE servers regardless of physical location. The management application resides in the HPE GreenLake cloud platform (access via <https://console.greenlake.hpe.com>) and leverages the HPE GreenLake architecture, security, and unified operations.

Security

- UEFI Secure Boot and Secure Start support
- Immutable Silicon Root of Trust
- FIPS 140-2 validation
- Common Criteria certification
- Configurable for PCI DSS compliance
- Advanced Encryption Standard (AES) and Triple Data Encryption Standard (3DES) on browser
- Support for Commercial National Security Algorithms (CNSA)
- iLO Security Modes
- Granular control over iLO interfaces
- Smart card (PIV/CAC) and Kerberos based 2-factor Authentication
- Tamper-free updates – components digitally signed and verified
- Secure Recovery – recover critical firmware to known good state on detection of compromised FW
- Ability to rollback firmware
- Secure erase of NAND
- TPM (Trusted Platform Module) 2.0 option
- Bezel Locking Kit
- Chassis Intrusion detection

HPE Trusted Platform Module

HPE Trusted Platform Module 2.0 is included on Pre-Configured models and can be enabled and disabled using the BIOS.

Notes: The TPM (Trusted Platform Module) is a microcontroller chip that can securely store artifacts used to authenticate the server platform. These artifacts can include passwords, certificates and encryption keys.

Warranty

This product is covered by a global limited warranty and supported by HPE Services and a worldwide network of HPE Authorized Channel Partners resellers. Hardware diagnostic support and repair is available for three years from date of purchase. Support for software and initial setup is available for 90 days from date of purchase. Enhancements to warranty services are available through HPE Services operational services or customized service agreements. Hard drives have either a one year or three year warranty; refer to the specific hard drive QuickSpecs for details.

Notes: Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite support with next business day response. Warranty repairs may be accomplished through the use of Customer Self Repair (CSR) parts. These parts fall into two categories: 1) Mandatory CSR parts are designed for easy replacement. A travel and labor charge will result when customers decline to replace a Mandatory CSR part; 2) Optional CSR parts are also designed for easy replacement but may involve added complexity. Customers may choose to have Hewlett Packard Enterprise replace Optional CSR parts at no charge. Additional information regarding worldwide limited warranty and technical support is available at:

<https://www.hpe.com/us/en/search-results.html?page=1&q=servers%20warranty&autocomplete=0>.



Standard Features

Server Management

HPE iLO Advanced

HPE iLO Advanced licenses offer smart remote functionality without compromise, for all HPE ProLiant servers. The license includes the full integrated remote console, virtual keyboard, video, and mouse (KVM), multi-user collaboration, console record and replay, and GUI-based and scripted virtual media and virtual folders. You can also activate the enhanced security and power management functionality.

HPE iLO Advanced Premium Security Edition

HPE iLO Advanced Premium Security Edition for iLO 5 includes iLO Advanced License plus high-end security modes, unique security capabilities, like Automatic FW recovery; Runtime FW verification, and Secure erase. Learn more about HPE iLO Advanced Premium Security Edition at: <https://h20195.www2.hpe.com/v2/default.aspx?cc=us&lc=en&oid=1010025876>

HPE OneView Advanced

HPE OneView brings a new level of automation to infrastructure management by taking a template driven approach to provisioning, updating, and integrating compute, storage, and networking infrastructure. It provides full-featured licenses which can be purchased for managing Gen8, Gen9 and Gen10 servers. To learn more visit <http://www.hpe.com/info/oneview>.

HPE Insight Cluster Management Utility (CMU)

HPE Insight Cluster Management Utility is a HyperScale management framework that includes software for the centralized provisioning, management and monitoring of nodes and infrastructure. Learn more at <http://www.hpe.com/info/cmu>.

Accelerator and GPGPU Information

Hewlett Packard Enterprise supports various accelerators on select HPE ProLiant servers to support different workloads. The accelerators enable seamless integration of GPU computing with HPE ProLiant servers for high-performance computing, large data center graphics, deep learning and virtual desktop deployments. These accelerators deliver all of the standard benefits of GPU computing while enabling maximum reliability and tight integration with system monitoring and management tools such as HPE Insight Cluster Management Utility.

Rack and Power Infrastructure

The story may end with servers, but it starts with the foundation that makes compute go – and business grow. We've reinvented our entire portfolio of rack and power products to make IT infrastructure more secure, more practical, and more efficient. In other words, we've created a stronger, smarter, and simpler infrastructure to help you get the most out of your IT equipment. As an industry leader, Hewlett Packard Enterprise is uniquely positioned to address the key concerns of power, cooling, cable management and system access.

HPE G2 Advanced and Enterprise Racks are perfect for the server room or today's modern data center with enhanced airflow and thermal management, flexible cable management, and a 10 year Warranty to support higher density computing.

HPE G2 PDUs offer reliable power in flexible form factors that operate at temperatures up to 60°, include color-coded outlets and load segments and a low-profile design for optimal access to the rack and support for dense rack environments.

HPE Uninterruptible Power Systems are cost-effective power protection for any type workload. Some UPSs include options for remote management and extended runtime modules so your critical dense data center is covered in power outages.

HPE KVM Solutions include a console and switches designed to work with your server and IT equipment reliably. We've got a cost-effective KVM switch for your first rack and multiple connection IP switches with remote management and security capabilities to keep your data center rack up and running.

Learn more about HPE Racks, KVM, PDUs and UPSs at [HPE Rack and Power Infrastructure](#).



Standard Features

One Config Simple (SCE)

SCE is a guided self-service tool to help sales and non-technical people provide customers with initial configurations in 3 to 5 minutes. You may then send the configuration on for configuration help, or use in your existing ordering processes. If you require "custom" rack configuration or configuration for products not available in SCE, please contact Hewlett Packard Enterprise Customer Business Center or an Authorized Partner for assistance

<https://h22174.www2.hpe.com/SimplifiedConfig/Welcome#>



Service and Support

HPE Services

No matter where you are in your digital transformation journey, you can count on HPE Services to deliver the expertise you need when, where and how you need it. From planning to deployment, ongoing operations and beyond, our experts can help you realize your digital ambitions.

<https://www.hpe.com/services>

Consulting Services

No matter where you are in your journey to hybrid cloud, experts can help you map out your next steps. From determining what workloads should live where, to handling governance and compliance, to managing costs, our experts can help you optimize your operations.

<https://www.hpe.com/services/consulting>

HPE Managed Services

HPE runs your IT operations, providing services that monitor, operate, and optimize your infrastructure and applications, delivered consistently and globally to give you unified control and let you focus on innovation.

[HPE Managed Services | HPE](#)

Operational services

Optimize your entire IT environment and drive innovation. Manage day-to-day IT operational tasks while freeing up valuable time and resources. Meet service-level targets and business objectives with features designed to drive better business outcomes.

<https://www.hpe.com/services/operational>

HPE Complete Care Service

HPE Complete Care Service is a modular, edge-to-cloud IT environment service designed to help optimize your entire IT environment and achieve agreed upon IT outcomes and business goals through a personalized experience. All delivered by an assigned team of HPE Services experts. HPE Complete Care Service provides:

- A complete coverage approach -- edge to cloud
- An assigned HPE team
- Modular and fully personalized engagement
- Enhanced Incident Management experience with priority access
- Digitally enabled and AI driven customer experience

<https://www.hpe.com/services/complecare>

HPE Tech Care Service

HPE Tech Care Service is the operational support service experience for HPE products. The service goes beyond traditional support by providing access to product specific experts, an AI driven digital experience, and general technical guidance to not only reduce risk but constantly search for ways to do things better. HPE Tech Care Service delivers a customer-centric, AI driven, and digitally enabled customer experience to move your business forward. HPE Tech Care Service is available in three response levels. Basic, which provides 9x5 business hour availability and a 2-hour response time. Essential which provides a 15-minute response time 24x7 for most enterprise level customers, and Critical which includes a 6-hour repair commitment where available and outage management response for severity 1 incidents.

<https://www.hpe.com/services/techcare>



Service and Support

HPE Lifecycle Services

HPE Lifecycle Services provide a variety of options to help maintain your HPE systems and solutions at all stages of the product lifecycle. A few popular examples include:

- Lifecycle Install and Startup Services: Various levels for physical installation and power on, remote access setup, installation and startup, and enhanced installation services with the operating system.
- HPE Firmware Update Analysis Service: Recommendations for firmware revision levels for selected HPE products, taking into account the relevant revision dependencies within your IT environment.
- HPE Firmware Update Implementation Service: Implementation of firmware updates for selected HPE server, storage, and solution products, taking into account the relevant revision dependencies within your IT environment.
- Implementation assistance services: Highly trained technical service specialists to assist you with a variety of activities, ranging from design, implementation, and platform deployment to consolidation, migration, project management, and onsite technical forums.
- HPE Service Credits: Access to prepaid services for flexibility to choose from a variety of specialized service activities, including assessments, performance maintenance reviews, firmware management, professional services, and operational best practices.

Notes: To review the list of Lifecycle Services available for your product go to:

<https://www.hpe.com/services/lifecycle>

For a list of the most frequently purchased services using service credits, see the [HPE Service Credits Menu](#)

Other Related Services from HPE Services

HPE Server Hardware Installation

Provides for the basic hardware installation of HPE branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner.

<https://h20195.www2.hpe.com/v2/Getdocument.aspx?docname=5981-9356enw>

HPE Installation and Startup Service

Provides for the installation of your HPE hardware according to product specifications including options. The HPE service delivery technician will connect the product to a LAN as appropriate and enable remote support to allow for automatic case creation for hardware failures. Installation and start up services also includes the installation of one supported operating system type (Windows® or Linux).

DC for Hyperscale

Complete Care for Hyperscale is available for Service Providers and HPC customers who use a scale out approach to computing with a high volume homogenous infrastructure and resilient architecture can take advantage of this environment support tailored to their operating model.

HPE Factory Express for Servers and storage

HPE Factory Express offers configuration, customization, integration and deployment services for HPE servers and storage products. Customers can choose how their factory solutions are built, tested, integrated, shipped and deployed.

Factory Express offers service packages for simple configuration, racking, installation, complex configuration and design services as well as individual factory services, such as image loading, asset tagging, and custom packaging. HPE products supported through Factory Express include a wide array of servers and storage: HPE Integrity, HPE ProLiant, HPE Apollo, HPE ProLiant Server Blades, HPE BladeSystem, HPE 9000 servers as well as the MSAXXX3PAR suite, XP, rackable tape libraries and configurable network switches.



Service and Support

HPE Education Services

Training and certification designed for IT and business professionals across all industries. Broad catalogue of course offerings to expand skills and proficiencies in topics ranging from cloud and cybersecurity to AI and DevOps. Create learning paths to expand proficiency in a specific subject. Schedule training in a way that works best for your business with flexible continuous learning options.

<https://www.hpe.com/services/training>

Defective Media Retention

An option available with HPE Complete Care Service and HPE Tech Care Service and applies only to Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

Consult your HPE Sales Representative or Authorized Channel Partner of choice for any additional questions and services options.

Parts and Materials

HPE will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product QuickSpecs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

How to Purchase Services

Services are sold by Hewlett Packard Enterprise and Hewlett Packard Enterprise Authorized Service Partners:

- Services for customers purchasing from HPE or an enterprise reseller are quoted using HPE order configuration tools.
- Customers purchasing from a commercial reseller can find services at <https://ssc.hpe.com/portal/site/ssc/>

AI Powered and Digitally Enabled Support Experience

Achieve faster time to resolution with access to product-specific resources and expertise through a digital and data driven customer experience

Sign into the HPE Support Center experience, featuring streamlined self-serve case creation and management capabilities with inline knowledge recommendations. You will also find personalized task alerts and powerful troubleshooting support through an intelligent virtual agent with seamless transition when needed to a live support agent.

<https://support.hpe.com/hpesc/public/home/signin>

Consume IT On Your Terms

HPE GreenLake edge-to-cloud platform brings the cloud experience directly to your apps and data wherever they are—the edge, colocations, or your data center. It delivers cloud services for on-premises IT infrastructure specifically tailored to your most demanding workloads. With a pay-per-use, scalable, point-and-click self-service experience that is managed for you, HPE GreenLake edge-to-cloud platform accelerates digital transformation in a distributed, edge-to-cloud world.

- Get faster time to market
- Save on TCO, align costs to business
- Scale quickly, meet unpredictable demand
- Simplify IT operations across your data centers and clouds

To learn more about HPE Services, please contact your Hewlett Packard Enterprise sales representative or Hewlett Packard Enterprise Authorized Channel Partner. Contact information for a representative in your area can be found at "Contact HPE"

<https://www.hpe.com/us/en/contact-hpe.html>

For more information

<http://www.hpe.com/services>



Configuration Information

This section lists some of the steps required to configure a Factory Integrated Model.

To ensure valid configurations are ordered, Hewlett Packard Enterprise recommends the use of an HPE approved configurator. Contact your local sales representative for information on configurable product offerings and requirements.

- Factory Integrated Models must start with a CTO Server.
- FIO indicates that this option is only available as a factory installable option.
- Some options may not be integrated at the factory. Contact your local sales representative for additional information

Step 1: Base Configuration (choose one of the following configurable models)

Network Choice (NC) Models

Network Choice models do not include embedded LOM. To enable networking capability please select a validated alternative NIC -OCP or PCIe- from the Core Options section.

CTO Models	HPE Alletra Storage Server 4120 24LFF Configure-to-order System	HPE Alletra Storage Server 4120 48SFF Configure-to-order System
SKU Number	P46252-B21	P46253-B21
TAA SKU*	P46252-B21#GTA	P46253-B21#GTA
Processor	Not included as standard	
DIMM Slots	24-DIMM slots	
Storage Controller	One or two SR 32-Port or two MR 16-port PCIe FIO Storage Controllers are required for the Cage 1 and Cage 2 drives and up to four per system for the upgrade drive cage(s).	Two SR 32-Port PCIe FIO Storage Controllers are required for the Cage 1 and Cage 2 drives and up to four per system for the upgrade drive cage
PCIe	Up to 8 PCIe slots	
Drive Cage - included	24 LFF – SAS 24Gb/SATA 6Gb	48 SFF – SAS 24Gb/SATA 6Gb
Network Controller	Choice of OCP or stand up cards Notes: No embedded networking.	
Fans	5 dual-rotor fan modules	
Management	Default: HPE iLO Standard with Intelligent Provisioning, HPE OneView Standard (requires download), HPE GreenLake for Compute Ops Management (subscription included)	
USB	Front: 1 USB 3.0 + iLO service port Rear: 2 USB 3.0 Internal: 1 USB 3.0	
Form Factor	2U Rack	
Warranty	3-year parts, 3-year labor, 3-year onsite support with next business day response.	

Notes: * HPE offers multiple Trade Agreement Act (TAA) compliant configurations to meet the needs of US Federal Government customers. These products are either manufactured or substantially transformed in a designated country.



Configuration Information

Step 2: Choose Required Options

Please select one or two matching processors for the 24LFF model, and two matching processors for the 48SFF model.

Notes:

- Mixing of 2 different processor models is not supported.
- Processors with TDP equal to or greater than 270W require High Performance Heat Sink Kit (P51832-B21).
- Processors with TDP lower than 270W require Standard Heat Sink Kit (P51833-B21).

Step 2a: Choose Processor Options

Processor Option Kits

Notes: All SKUs below ship with processor only. Adequate heatsinks (standard or high performance) must be selected.

5th Generation Intel Xeon-Platinum

Description

Description	SKU
Intel Xeon-Platinum 8568Y+ 2.3GHz 48-core 350W Processor Kit for HPE Alletra Storage Server 41X0	P67405-B21
Intel Xeon-Platinum 8562Y+ 2.8GHz 32-core 300W Processor Kit for HPE Alletra Storage Server 41X0	P67408-B21
Intel Xeon-Platinum 8558 2.1GHz 48-core 330W Processor Kit for HPE Alletra Storage Server 41X0	P67406-B21

5th Generation Intel Xeon-Gold

Description

Description	SKU
Intel Xeon-Gold 6554S 2.2GHz 36-core 270W Processor Kit for HPE Alletra Storage Server 41X0	P67407-B21
Intel Xeon-Gold 6548Y+ 2.5GHz 32-core 250W Processor Kit for HPE Alletra Storage Server 41X0	P67410-B21
Intel Xeon-Gold 6544Y 3.6GHz 16-core 270W Processor Kit for HPE Alletra Storage Server 41X0	P67417-B21
Intel Xeon-Gold 6542Y 2.9GHz 24-core 250W Processor Kit for HPE Alletra Storage Server 41X0	P67415-B21
Intel Xeon-Gold 6538Y+ 2.2GHz 32-core 225W Processor Kit for HPE Alletra Storage Server 41X0	P67409-B21
Intel Xeon-Gold 6538N 2.1GHz 32-core 205W Processor Kit for HPE Alletra Storage Server 41X0	P67412-B21
Intel Xeon-Gold 6534 3.9GHz 8-core 195W Processor Kit for HPE Alletra Storage Server 41X0	P67401-B21
Intel Xeon-Gold 6530 2.1GHz 32-core 270W Processor Kit for HPE Alletra Storage Server 41X0	P67411-B21
Intel Xeon-Gold 6526Y 2.8GHz 16-core 195W Processor Kit for HPE Alletra Storage Server 41X0	P67418-B21
Intel Xeon-Gold 5520+ 2.2GHz 28-core 205W Processor Kit for HPE Alletra Storage Server 41X0	P67413-B21
Intel Xeon-Gold 5515+ 3.2GHz 8-core 165W Processor Kit for HPE Alletra Storage Server 41X0	P67402-B21
Intel Xeon-Gold 5512U 2.1GHz 28-core 185W Processor Kit for HPE Alletra Storage Server 41X0	P67414-B21

5th Generation Intel Xeon-Silver

Description

Description	SKU
Intel Xeon-Silver 4516Y+ 2.2GHz 24-core 185W Processor Kit for HPE Alletra Storage Server 41X0	P67416-B21
Intel Xeon-Silver 4514Y 2.0GHz 16-core 150W Processor Kit for HPE Alletra Storage Server 41X0	P67419-B21
Intel Xeon-Silver 4510 2.4GHz 12-core 150W Processor Kit for HPE Alletra Storage Server 41X0	P67420-B21
Intel Xeon-Silver 4509Y 2.6GHz 8-core 125W Processor Kit for HPE Alletra Storage Server 41X0	P67403-B21

5th Generation Intel Xeon-Bronze

Description

Description	SKU
Intel Xeon-Bronze 3508U 2.1GHz 8-core 125W Processor Kit for HPE Alletra Storage Server 41X0	P67404-B21



Configuration Information

4th Generation Intel Xeon-Platinum

Description

	SKU
Intel Xeon-Platinum 9468 2.1GHz 48-core 350W Processor Kit for HPE Alletra Storage Server 41X0	P50810-B21
Intel Xeon-Platinum 9462 2.7GHz 32-core 350W Processor Kit for HPE Alletra Storage Server 41X0	P50814-B21
Intel Xeon-Platinum 9460 2.2GHz 40-core 350W Processor Kit for HPE Alletra Storage Server 41X0	P50815-B21
Intel Xeon-Platinum 8468 2.1GHz 48-core 350W Processor Kit for HPE Alletra Storage Server 41X0	P51959-B21
Intel Xeon-Platinum 8462Y+ 2.8GHz 32-core 300W Processor Kit for HPE Alletra Storage Server 41X0	P50799-B21
Intel Xeon-Platinum 8460Y+ 2.0GHz 40-core 300W Processor Kit for HPE Alletra Storage Server 41X0	P50800-B21
Intel Xeon-Platinum 8452Y 2.0GHz 36-core 300W Processor Kit for HPE Alletra Storage Server 41X0	P50807-B21

4th Generation Intel Xeon-Gold

Description

	SKU
Intel Xeon-Gold 6454S 2.2GHz 32-core 270W Processor Kit for HPE Alletra Storage Server 41X0	P50809-B21
Intel Xeon-Gold 6448Y 2.1GHz 32-core 225W Processor Kit for HPE Alletra Storage Server 41X0	P50796-B21
Intel Xeon-Gold 6444Y 3.6GHz 16-core 270W Processor Kit for HPE Alletra Storage Server 41X0	P50798-B21
Intel Xeon-Gold 6442Y 2.6GHz 24-core 225W Processor Kit for HPE Alletra Storage Server 41X0	P50795-B21
Intel Xeon-Gold 6438Y+ 2.0GHz 32-core 205W Processor Kit for HPE Alletra Storage Server 41X0	P50806-B21
Intel Xeon-Gold 6434 3.7GHz 8-core 205W Processor Kit for HPE Alletra Storage Server 41X0	P50797-B21
Intel Xeon-Gold 6430 2.1GHz 32-core 270W Processor Kit for HPE Alletra Storage Server 41X0	P50805-B21
Intel Xeon-Gold 6426Y 2.5GHz 16-core 185W Processor Kit for HPE Alletra Storage Server 41X0	P50794-B21
Intel Xeon-Gold 6414U 2.0GHz 32-core 250W Processor Kit for HPE Alletra Storage Server 41X0	P50813-B21
Intel Xeon-Gold 5420+ 2.0GHz 28-core 205W Processor Kit for HPE Alletra Storage Server 41X0	P50804-B21
Intel Xeon-Gold 5418Y 2.0GHz 24-core 185W Processor Kit for HPE Alletra Storage Server 41X0	P50803-B21
Intel Xeon-Gold 5418N 1.8GHz 24-core 165W Processor Kit for HPE Alletra Storage Server 41X0	P50816-B21
Intel Xeon-Gold 5416S 2.0GHz 16-core 150W Processor Kit for HPE Alletra Storage Server 41X0	P50808-B21
Intel Xeon-Gold 5415+ 2.9GHz 8-core 150W Processor Kit for HPE Alletra Storage Server 41X0	P50793-B21
Intel Xeon-Gold 5412U 2.1GHz 24-core 185W Processor Kit for HPE Alletra Storage Server 41X0	P50812-B21

4th Generation Intel Xeon-Silver

Description

	SKU
Intel Xeon-Silver 4416+ 2.0GHz 20-core 165W Processor Kit for HPE Alletra Storage Server 41X0	P50802-B21
Intel Xeon-Silver 4410Y 2.0GHz 12-core 150W Processor Kit for HPE Alletra Storage Server 41X0	P50801-B21

4th Generation Intel Xeon-Bronze

Description

	SKU
Intel Xeon-Bronze 3408U 1.8GHz 8-core 125W Processor Kit for HPE Alletra Storage Server 41X0	P50811-B21

Step 2b: Choose Memory Options

Please select one or more memory from below.

For additional information, please see the [HPE DDR5 Smart Memory QuickSpecs](#).

Notes:

- The maximum memory speed and capacity is a function of the memory type, memory configuration, and processor model.
- Quantity of memory DIMMs selected per socket must be 0, 1, 2, 4, 6, 8, or 12.
- The 5600 MT/s Memory SKUs are supported for 5th Gen processors only
- The 4800 MT/s Memory SKUs are supported for 4th Gen processors only



Configuration Information

Registered DIMMs (RDIMMs)

Notes:

- Mixing of 3DS and non-3DS DIMMs not allowed.
- Rank Mixing is not supported

Description

	SKU
HPE 16GB (1x16GB) Single Rank x8 DDR5-5600 CAS-46-45-45 EC8 Registered Smart Memory Kit	P64705-K21
HPE 32GB (1x32GB) Dual Rank x8 DDR5-5600 CAS-46-45-45 EC8 Registered Smart Memory Kit	P64706-K21
HPE 64GB (1x64GB) Dual Rank x4 DDR5-5600 CAS-46-45-45 EC8 Registered Smart Memory Kit	P64707-K21
HPE 96GB (1x96GB) Dual Rank x4 DDR5-5600 CAS-46-45-45 EC8 Registered Smart Memory Kit	P64708-K21

Notes: Do not support SPR EE LCC SKUs. Do not support quantity 2 or 4 per CPU socket.

HPE 128GB (1x128GB) Quad Rank x4 DDR5-5600 CAS-52-45-45 EC8 Registered 3DS Smart Memory Kit	P64709-K21
HPE 128GB (1x128GB) Dual Rank x4 DDR5-5600 CAS-46-45-45 EC8 Registered Smart Memory Kit	P69976-K21
HPE 16GB (1x16GB) Single Rank x8 DDR5-4800 CAS-40-39-39 EC8 Registered Smart Memory Kit	P43322-K21
HPE 32GB (1x32GB) Dual Rank x8 DDR5-4800 CAS-40-39-39 EC8 Registered Smart Memory Kit	P43328-K21
HPE 64GB (1x64GB) Dual Rank x4 DDR5-4800 CAS-40-39-39 EC8 Registered Smart Memory Kit	P43331-K21
HPE 128GB (1x128GB) Quad Rank x4 DDR5-4800 CAS-46-39-39 EC8 Registered 3DS Smart Memory Kit	P43334-K21
HPE 128GB (1x128GB) Dual Rank x4 DDR5-4800 CAS-40-39-39 EC8 Registered Smart Memory Kit	P69974-K21
HPE 256GB (1x256GB) Octal Rank x4 DDR5-4800 CAS-46-39-39 EC8 Registered 3DS Smart Memory Kit	P43337-K21

Notes: Support limited to 25°C maximum inlet temperature.

Step 2c: Choose Power Supplies

Please select one or two power supplies from below.

Notes: Mixing of 2 different power supplies are NOT allowed.

HPE Flex Slot Power Supplies

HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	P38995-B21
HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit	P03178-B21
HPE 1600W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	P38997-B21
HPE 1800W-2200W Flex Slot Titanium Hot Plug Power Supply Kit	P44712-B21
Notes: Only supports high line voltage (200 VAC to 240 VAC).	
HPE 1600W Flex Slot -48VDC Hot Plug Power Supply Kit	P17023-B21

Step 3: Choose Additional (FIO) Factory Integratable Options

Each of the following may be selected if desired at time of factory integration

Description

	SKU
HPE Smart Memory Fast Fault Tolerance FIO Setting	875293-B21

Notes:

- Enables Fast Fault Tolerance mode, an HPE Memory RAS feature introduced in HPE Gen10 servers that survives up to two DRAM failures.
- This RAS feature combines Adaptive Double DRAM Device Correction (ADDC) with HPE Advanced Error Detection Technology, resulting in significantly better memory reliability and availability than what ADDDC provides on its own. For more information see our [Memory RAS feature technical whitepaper](#).



Configuration Information

HPE Security Options

HPE Server Security Optimized Service for HPE ProLiant (R9S59A) is an optional security upgrade intended for agencies and regulated industries with enhanced security and compliance needs. Applying this option to a HPE Alletra Storage Server 41X0 CTO system ensures it is hardened by turning on advanced safeguards in place against cyber-exploits throughout the server lifecycle. An iLO Advanced License required for High Security Mode and compatible intrusion detection device option kits are prerequisites for the full optimization service.

Step 4: Management software

Select your choice of cloud-native management or on-premises management software.

HPE Greenlake for Compute Ops Management for cloud-native management

Notes: HPE Greenlake for Compute Ops Management for cloud-native management of Alletra Storage Servers, as well as ProLiant servers. The SKUs below are for Alletra Storage Servers specifically, and are billed upfront. If you want to be billed monthly or annually, please order R6Z73AAE standalone.

Recommended SKU

Description

HPE Compute Ops Management Enhanced 5-year Upfront Alletra 4000 SaaS

SKU

S1E13AAE

Alternative SKUs

HPE Compute Ops Management Enhanced 3-year Upfront Alletra 4000 SaaS

SKU

S1E12AAE

Required SKU when ordering through GreenLake Flex

HPE Compute Ops Management Flex with Alletra 4000 Tracking

SKU

S4P39AAE

Notes: Both the tracking SKU above as well as one of the COM SaaS SKUs (S1E12 AAE or S1E13AAE) are needed to allow COM to be included and transacted as part of a GL Flex solution and contracts.

HPE OneView

HPE OneView including 3yr 24x7 Support Flexible Quantity E-LTU

SKU

E5Y35AAE

HPE OneView w/o iLO including 3yr 24x7 Support Flexible Quantity E-LTU

P8B26AAE



Core Options

Some options may not be integrated at the factory. To ensure only valid configurations are ordered, Hewlett Packard Enterprise recommends the use of a Hewlett Packard Enterprise approved configurator. Contact your local sales representative for additional information.

HPE Unique Options

Cooling Options

Description	SKU
HPE Alletra Storage Server 4120 High Performance Heat Sink Kit	P51832-B21
Notes: Required for processors with a TDP equal or greater than 270W.	
HPE Alletra Storage Server 4120 Standard Heat Sink Kit	P51833-B21

System FIO Storage Controllers

HPE Alletra Storage Server 41X0 SR 32-port PCIe FIO Storage Controller	P61479-B21
HPE Alletra Storage Server 41X0 MR 16-port PCIe FIO Storage Controller	P61480-B21

System FIO Storage Controller Mode for 24LFF Cage2

HPE Alletra Storage Server 4120 24LFF Cage 2 to CPU1 Slot 8 FIO Controller Mode	P59379-B21
Notes: Required for single 32-port controller configured for drive cage1 and cage2 in one system.	
HPE Alletra Storage Server 4120 24LFF Cage 2 to CPU2 Slot 7 FIO Controller Mode	P59380-B21
Notes: Required for two processors and two controllers configured for drive cage1 and cage2 in one system.	

Primary Risers

Notes: The Primary location can be either PCIe Primary Riser Kit (P50871-B21) or 2LFF SAS/SATA LP Primary Drive Cage Kit (P50873-B21).

HPE Alletra Storage Server 4120 PCIe Primary Riser Kit	P50871-B21
HPE Alletra Storage Server 4120 2LFF SAS/SATA LP Primary Drive Cage Kit	P50873-B21

Secondary Risers

Notes: The Secondary location can be either PCIe Secondary Riser Kit (P50872-B21) or 2LFF SAS/SATA LP Secondary Drive Cage Kit (P51783-B21).

HPE Alletra Storage Server 4120 PCIe Secondary Riser Kit	P50872-B21
HPE Alletra Storage Server 4120 2LFF SAS/SATA LP Secondary Drive Cage Kit	P51783-B21

Rear Drive Cage Storage Upgrades

HPE Alletra Storage Server 4120 6SFF x4 Tri-Mode U.3 BC Rear Drive Cage Upgrade Kit	P51784-B21
Notes: The 6SFF x4 Tri-Mode U.3 BC Rear Drive Cage Upgrade Kit (P51784-B21) occupies both the Primary and Secondary locations and includes 1U Primary and Secondary Riser.	
HPE Alletra Storage Server 4120 12EDSFF E3.S 1Tx4 Rear Drive Cage Upgrade Kit	P50875-B21
Notes: The 12EDSFF E3.S x4 Rear Drive Cage Upgrade Kit (P50875-B21) occupies both the Primary and Secondary locations and includes 1U Primary and Secondary Riser.	

Rear Drive Cage Cables

Notes: One of the Rear Drive Cage Cable must be selected when Rear Drive Cage Upgrade SKU is selected.

HPE Alletra Storage Server 4120 6SFF Rear Drive Cage Balanced NVMe Direct Attach Cable Kit	P50876-B21
Notes: When this SKU is selected, the 2nd processor is required.	
HPE Alletra Storage Server 4120 6SFF Rear Drive Cage CPU1 NVMe Direct Attach Cable Kit	P50877-B21
HPE Alletra Storage Server 4120 6SFF Rear Drive Cage CPU1 Controller Cable Kit	P50878-B21
Notes: When this SKU is selected, additional one storage controller is required.	



Core Options

Description

SKU

HPE Alletra Storage Server 4120 6SFF Rear Drive Cage Balanced Slot 3/6 Controller Cable Kit P50879-B21

Notes: When this SKU is selected, the 2nd processor and additional two storage controllers are required.

HPE Alletra Storage Server 4120 6SFF Rear Drive Cage Balanced Slot 7/8 Controller Cable Kit P50880-B21

Notes: When this SKU is selected, the 2nd processor and two storage controllers are required.

HPE Alletra Storage Server 4120 12EDSFF Rear Drive Cage Balanced NVMe Direct Attach Cable Kit P50881-B21

Notes:

- When this SKU is selected, the 2nd processor is required.
- When this SKU is selected, the OCP Upgrade Cable Kits (P51942-B21 and P51943-B21) cannot be selected.

HPE Alletra Storage Server 4120 12EDSFF Rear Drive Cage Balanced Controller Cable Kit P50882-B21

Notes: When this SKU is selected, the 2nd processor and two storage controllers are required.

System OCP Options

HPE Alletra Storage Server 4120 OCP2 x8 CPU1 Enablement Kit P51944-B21

Notes: This SKU can enable OCP2 slot bandwidth X8 PCIe Gen5 from the 1st processor.

HPE Alletra Storage Server 4120 OCP2 x8 CPU2 Enablement Kit P51945-B21

Notes: This SKU can enable OCP2 slot bandwidth X8 PCIe Gen5 from the 2nd processor, and the 2nd processor is required.

HPE Alletra Storage Server 4120 OCP1 Upgrade Cable Kit P51942-B21

Notes: This SKU can improve the OCP1 slot bandwidth from X8 to X16 PCIe Gen5.

HPE Alletra Storage Server 4120 OCP2 Upgrade Cable Kit P51943-B21

Notes: This SKU can improve the OCP2 slot bandwidth from X8 to X16 PCIe Gen5, and the 2nd processor is required.

HPE OCP Thermal Enhancement Kit P28727-B21

Notes: This SKU is required when OCP options requiring better thermal condition and the PCIe slot above the OCP slot will be occupied by this SKU.

System Racking Options

HPE 2U Shelf-Mount Adjustable Rail Kit 822731-B21

HPE Apollo 4200 Gen9 FIO Strap Shipping Bracket 822640-B21

Notes: This SKU is used for shipping servers that are integrated in a rack.

System NVMe Boot Device Enablement Options

HPE Alletra Storage Server 4120 NVMe M.2 Enablement Kit P50885-B21

Notes: This SKU is required when HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device (P48183-B21) is installed.

Security

Description

SKU

HPE Gen11 2U Storage Bezel Kit P51688-B21

HPE Bezel Lock Kit 875519-B21



Core Options

HPE Processors

Please select one or two matching processors.

Notes:

- Mixing of 2 different processor models is not supported.
- Processors with TDP equal to or greater than 270W require High Performance Heat Sink Kit (P51832-B21).
- Processors with TDP lower than 270W require Standard Heat Sink Kit (P51833-B21).

Processor Option Kits

Notes: All SKUs below ship with processor only. Adequate heatsinks (standard, or high performance) must be selected.

5th Generation Intel Xeon-Platinum

Description

	SKU
Intel Xeon-Platinum 8568Y+ 2.3GHz 48-core 350W Processor Kit for HPE Alletra Storage Server 41X0	P67405-B21
Intel Xeon-Platinum 8562Y+ 2.8GHz 32-core 300W Processor Kit for HPE Alletra Storage Server 41X0	P67408-B21
Intel Xeon-Platinum 8558 2.1GHz 48-core 330W Processor Kit for HPE Alletra Storage Server 41X0	P67406-B21

5th Generation Intel Xeon-Gold

Intel Xeon-Gold 6554S 2.2GHz 36-core 270W Processor Kit for HPE Alletra Storage Server 41X0	P67407-B21
Intel Xeon-Gold 6548Y+ 2.5GHz 32-core 250W Processor Kit for HPE Alletra Storage Server 41X0	P67410-B21
Intel Xeon-Gold 6544Y 3.6GHz 16-core 270W Processor Kit for HPE Alletra Storage Server 41X0	P67417-B21
Intel Xeon-Gold 6542Y 2.9GHz 24-core 250W Processor Kit for HPE Alletra Storage Server 41X0	P67415-B21
Intel Xeon-Gold 6538Y+ 2.2GHz 32-core 225W Processor Kit for HPE Alletra Storage Server 41X0	P67409-B21
Intel Xeon-Gold 6538N 2.1GHz 32-core 205W Processor Kit for HPE Alletra Storage Server 41X0	P67412-B21
Intel Xeon-Gold 6534 3.9GHz 8-core 195W Processor Kit for HPE Alletra Storage Server 41X0	P67401-B21
Intel Xeon-Gold 6530 2.1GHz 32-core 270W Processor Kit for HPE Alletra Storage Server 41X0	P67411-B21
Intel Xeon-Gold 6526Y 2.8GHz 16-core 195W Processor Kit for HPE Alletra Storage Server 41X0	P67418-B21
Intel Xeon-Gold 5520+ 2.2GHz 28-core 205W Processor Kit for HPE Alletra Storage Server 41X0	P67413-B21
Intel Xeon-Gold 5515+ 3.2GHz 8-core 165W Processor Kit for HPE Alletra Storage Server 41X0	P67402-B21
Intel Xeon-Gold 5512U 2.1GHz 28-core 185W Processor Kit for HPE Alletra Storage Server 41X0	P67414-B21

5th Generation Intel Xeon-Silver

Intel Xeon-Silver 4516Y+ 2.2GHz 24-core 185W Processor Kit for HPE Alletra Storage Server 41X0	P67416-B21
Intel Xeon-Silver 4514Y 2.0GHz 16-core 150W Processor Kit for HPE Alletra Storage Server 41X0	P67419-B21
Intel Xeon-Silver 4510 2.4GHz 12-core 150W Processor Kit for HPE Alletra Storage Server 41X0	P67420-B21
Intel Xeon-Silver 4509Y 2.6GHz 8-core 125W Processor Kit for HPE Alletra Storage Server 41X0	P67403-B21

5th Generation Intel Xeon-Bronze

Intel Xeon-Bronze 3508U 2.1GHz 8-core 125W Processor Kit for HPE Alletra Storage Server 41X0	P67404-B21
--	------------

4th Generation Intel Xeon-Platinum

Intel Xeon-Platinum 9468 2.1GHz 48-core 350W Processor Kit for HPE Alletra Storage Server 41X0	P50810-B21
Intel Xeon-Platinum 9462 2.7GHz 32-core 350W Processor Kit for HPE Alletra Storage Server 41X0	P50814-B21
Intel Xeon-Platinum 9460 2.2GHz 40-core 350W Processor Kit for HPE Alletra Storage Server 41X0	P50815-B21
Intel Xeon-Platinum 8468 2.1GHz 48-core 350W Processor Kit for HPE Alletra Storage Server 41X0	P51959-B21
Intel Xeon-Platinum 8462Y+ 2.8GHz 32-core 300W Processor Kit for HPE Alletra Storage Server 41X0	P50799-B21



Core Options

Description	SKU
Intel Xeon-Platinum 8460Y+ 2.0GHz 40-core 300W Processor Kit for HPE Alletra Storage Server 41X0	P50800-B21
Intel Xeon-Platinum 8452Y 2.0GHz 36-core 300W Processor Kit for HPE Alletra Storage Server 41X0	P50807-B21
4th Generation Intel Xeon-Gold	
Intel Xeon-Gold 6454S 2.2GHz 32-core 270W Processor Kit for HPE Alletra Storage Server 41X0	P50809-B21
Intel Xeon-Gold 6448Y 2.1GHz 32-core 225W Processor Kit for HPE Alletra Storage Server 41X0	P50796-B21
Intel Xeon-Gold 6444Y 3.6GHz 16-core 270W Processor Kit for HPE Alletra Storage Server 41X0	P50798-B21
Intel Xeon-Gold 6442Y 2.6GHz 24-core 225W Processor Kit for HPE Alletra Storage Server 41X0	P50795-B21
Intel Xeon-Gold 6438Y+ 2.0GHz 32-core 205W Processor Kit for HPE Alletra Storage Server 41X0	P50806-B21
Intel Xeon-Gold 6434 3.7GHz 8-core 205W Processor Kit for HPE Alletra Storage Server 41X0	P50797-B21
Intel Xeon-Gold 6430 2.1GHz 32-core 270W Processor Kit for HPE Alletra Storage Server 41X0	P50805-B21
Intel Xeon-Gold 6426Y 2.5GHz 16-core 185W Processor Kit for HPE Alletra Storage Server 41X0	P50794-B21
Intel Xeon-Gold 6414U 2.0GHz 32-core 250W Processor Kit for HPE Alletra Storage Server 41X0	P50813-B21
Intel Xeon-Gold 5420+ 2.0GHz 28-core 205W Processor Kit for HPE Alletra Storage Server 41X0	P50804-B21
Intel Xeon-Gold 5418Y 2.0GHz 24-core 185W Processor Kit for HPE Alletra Storage Server 41X0	P50803-B21
Intel Xeon-Gold 5418N 1.8GHz 24-core 165W Processor Kit for HPE Alletra Storage Server 41X0	P50816-B21
Intel Xeon-Gold 5416S 2.0GHz 16-core 150W Processor Kit for HPE Alletra Storage Server 41X0	P50808-B21
Intel Xeon-Gold 5415+ 2.9GHz 8-core 150W Processor Kit for HPE Alletra Storage Server 41X0	P50793-B21
Intel Xeon-Gold 5412U 2.1GHz 24-core 185W Processor Kit for HPE Alletra Storage Server 41X0	P50812-B21
4th Generation Intel Xeon-Silver	
Intel Xeon-Silver 4416+ 2.0GHz 20-core 165W Processor Kit for HPE Alletra Storage Server 41X0	P50802-B21
Intel Xeon-Silver 4410Y 2.0GHz 12-core 150W Processor Kit for HPE Alletra Storage Server 41X0	P50801-B21
4th Generation Intel Xeon-Bronze	
Intel Xeon-Bronze 3408U 1.8GHz 8-core 125W Processor Kit for HPE Alletra Storage Server 41X0	P50811-B21

HPE Memory

Please select two or more memory DIMMs from below.

For additional information, please see the [HPE DDR5 Smart Memory QuickSpecs](#).

Notes:

- The maximum memory speed and capacity is a function of the memory type, memory configuration, and processor model.
- Quantity of memory DIMMs selected per socket must be 0, 1, 2, 4, 6, 8, or 12 per socket.
- The 5600 MT/s Memory SKUs are supported for 5th Gen processors only
- The 4800 MT/s Memory SKUs are supported for 4th Gen processors only

HPE DDR5 Memory

Registered DIMMs (RDIMMs)

Notes:

- Mixing of 3DS and non-3DS DIMMs not allowed.
- Rank and capacity mixing of DIMMs is not

Description

Description	SKU
HPE 16GB (1x16GB) Single Rank x8 DDR5-5600 CAS-46-45-45 EC8 Registered Smart Memory Kit	P64705-K21
HPE 32GB (1x32GB) Dual Rank x8 DDR5-5600 CAS-46-45-45 EC8 Registered Smart Memory Kit	P64706-K21

Core Options

Description

	SKU
HPE 64GB (1x64GB) Dual Rank x4 DDR5-5600 CAS-46-45-45 EC8 Registered Smart Memory Kit	P64707-K21
HPE 96GB (1x96GB) Dual Rank x4 DDR5-5600 CAS-46-45-45 EC8 Registered Smart Memory Kit	P64708-K21
Notes: Do not support SPR EE LCC SKUs. Do not support quantity 2 or 4 per CPU socket.	
HPE 128GB (1x128GB) Quad Rank x4 DDR5-5600 CAS-52-45-45 EC8 Registered 3DS Smart Memory Kit	P64709-K21
HPE 128GB (1x128GB) Dual Rank x4 DDR5-5600 CAS-46-45-45 EC8 Registered Smart Memory Kit	P69976-K21
HPE 16GB (1x16GB) Single Rank x8 DDR5-4800 CAS-40-39-39 EC8 Registered Smart Memory Kit	P43322-K21
HPE 32GB (1x32GB) Dual Rank x8 DDR5-4800 CAS-40-39-39 EC8 Registered Smart Memory Kit	P43328-K21
HPE 64GB (1x64GB) Dual Rank x4 DDR5-4800 CAS-40-39-39 EC8 Registered Smart Memory Kit	P43331-K21
HPE 128GB (1x128GB) Quad Rank x4 DDR5-4800 CAS-46-39-39 EC8 Registered 3DS Smart Memory Kit	P43334-K21
HPE 128GB (1x128GB) Dual Rank x4 DDR5-4800 CAS-40-39-39 EC8 Registered Smart Memory Kit	P69974-K21
HPE 256GB (1x256GB) Octal Rank x4 DDR5-4800 CAS-46-39-39 EC8 Registered 3DS Smart Memory Kit	P43337-K21

Notes: Support limited to 25°C maximum inlet temperature.

HPE Boot Device

Description

	SKU
HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device	P48183-B21
HPE Alletra Storage Server 41X0 Direct Attach NVMe M.2 OS Boot Device	P60350-B21
Notes: No NVMe M.2 SSD included and requires at least one NVMe SSD.	
HPE 480GB NVMe Gen3 Mainstream Performance Read Intensive M.2 Multi Vendor SSD	P40513-B21
HPE 960GB NVMe Gen3 Mainstream Performance Read Intensive M.2 Multi Vendor SSD	P40514-B21
HPE 1.92TB NVMe Gen3 Mainstream Performance Read Intensive M.2 Multi Vendor SSD	P40515-B21
HPE 480GB NVMe Gen4 Mainstream Performance Read Intensive M.2 PM9A3 SSD	P69543-K21
HPE Alletra Storage Server 4120 NVMe M.2 Enablement Kit	P50885-B21

Notes: Required when NVMe Boot Device is selected.

HPE Drives

Midline - 12G SAS - LFF Drives

Description

	SKU
HPE 24TB SAS 12G Business Critical 7.2K LFF LP 1-year Warranty Helium 512e ISE Multi Vendor HDD	P68583-K21
HPE 20TB SAS 12G Business Critical 7.2K LFF LP 1-year Warranty Helium 512e ISE Multi Vendor HDD	P53553-K21
HPE 18TB SAS 12G Business Critical 7.2K LFF LP 1-year Warranty Helium 512e ISE Multi Vendor HDD	P37669-K21
HPE 16TB SAS 12G Business Critical 7.2K LFF LP 1-year Warranty Helium 512e ISE Multi Vendor HDD	P23608-K21
HPE 12TB SAS 12G Business Critical 7.2K LFF LP 1-year Warranty Helium 512e Multi Vendor HDD	881781-K21
HPE 10TB SAS 12G Business Critical 7.2K LFF LP 1-year Warranty 512e ISE Multi Vendor HDD	P53556-K21
HPE 8TB SAS 12G Business Critical 7.2K LFF LP 1-year Warranty 512e Multi Vendor HDD	834031-K21
HPE 6TB SAS 12G Business Critical 7.2K LFF LP 1-year Warranty 512e Multi Vendor HDD	861746-K21
HPE 4TB SAS 12G Business Critical 7.2K LFF LP 1-year Warranty Multi Vendor HDD	833928-K21
HPE 2TB SAS 12G Business Critical 7.2K LFF LP 1-year Warranty Multi Vendor HDD	833926-K21



Core Options

Midline - 12G SAS - LFF Self-encrypting (SED) Drives

Description

	SKU
HPE 16TB SAS 12G Business Critical 7.2K LFF LP 1-year Warranty 512e Self-encrypting FIPS HDD	P28626-K21
HPE 8TB SAS 12G Business Critical 7.2K LFF LP 1-year Warranty 512e Self-encrypting FIPS Private HDD	P28634-K21
HPE 4TB SAS 12G Business Critical 7.2K LFF LP 1-year Warranty Self-encrypting FIPS Private HDD	P28642-K21

Midline - 6G SATA - LFF Drives

HPE 24TB SATA 6G Business Critical 7.2K LFF LP 1-year Warranty Helium 512e ISE Multi Vendor HDD	P68585-K21
HPE 20TB SATA 6G Business Critical 7.2K LFF LP 1-year Warranty Helium 512e ISE Multi Vendor HDD	P53554-K21
HPE 16TB SATA 6G Business Critical 7.2K LFF LP 1-year Warranty Helium 512e ISE Multi Vendor HDD	P23449-K21
HPE 12TB SATA 6G Business Critical 7.2K LFF LP 1-year Warranty Helium 512e Multi Vendor HDD	881787-K21
HPE 10TB SATA 6G Business Critical 7.2K LFF LP 1-year Warranty 512e ISE Multi Vendor HDD	P53557-K21
HPE 8TB SATA 6G Business Critical 7.2K LFF LP 1-year Warranty 512e Multi Vendor HDD	834028-K21
HPE 6TB SATA 6G Business Critical 7.2K LFF LP 1-year Warranty 512e Multi Vendor HDD	861742-K21
HPE 4TB SATA 6G Business Critical 7.2K LFF LP 1-year Warranty Multi Vendor HDD	861683-K21
HPE 2TB SATA 6G Business Critical 7.2K LFF LP 1-year Warranty Multi Vendor HDD	861681-K21
HPE 1TB SATA 6G Business Critical 7.2K LFF LP 1-year Warranty Multi Vendor HDD	861686-K21

Midline - 6G SATA - LFF Self-Encrypting Drives

HPE 8TB SATA 6G Business Critical 7.2K LFF LP 1-year Warranty 512e Self-encrypting FIPS HDD	P28630-K21
HPE 4TB SATA 6G Business Critical 7.2K LFF LP 1-year Warranty Self-encrypting FIPS Private HDD	P28638-K21

Enterprise - 12G SAS - SFF Drives

HPE 2.4TB SAS 12G Mission Critical 10K SFF BC 3-year Warranty 512e Multi Vendor HDD	P28352-K21
HPE 1.2TB SAS 12G Mission Critical 10K SFF BC 3-year Warranty Multi Vendor HDD	P28586-K21
HPE 300GB SAS 12G Mission Critical 10K SFF BC 3-year Warranty Multi Vendor HDD	P40430-K21
HPE 600GB SAS 12G Mission Critical 10K SFF BC 3-year Warranty Multi Vendor HDD	P53561-K21
HPE 1.8TB SAS 12G Mission Critical 10K SFF BC 3-year Warranty 512e Multi Vendor HDD	P53562-K21

SED (Self-Encryption Drive)

HPE 2.4TB SAS 12G Mission Critical 10K SFF BC 3-year Warranty 512e Self-encrypting HDD	P28618-K21
HPE 1.2TB SAS 12G Mission Critical 10K SFF BC 3-year Warranty Self-encrypting FIPS HDD	P28622-K21

SSD Selection

For SSD selection guidance, please visit <https://ssd.hpe.com/>

For SSDs with optimal product availability, HPE advocates SSDs from the list located here:

<http://www.hpe.com/products/recommend>.

Mixed Use – PCIe/NVMe EDSFF - E3S EC1 EDSFF Solid State Drives

Description

	SKU
HPE 3.2TB NVMe Gen5 High Performance Mixed Use E3S EC1 EDSFF SPDM CM7 SSD	P61191-K21



Core Options

Description

SKU

HPE 6.4TB NVMe Gen5 High Performance Mixed Use E3S EC1 EDSFF SPDM CM7 SSD	P61195-K21
HPE 1.6TB NVMe Gen5 Mainstream Performance Mixed Use E3S EC1 CD8P SSD	P69241-K21
HPE 3.2TB NVMe Gen5 Mainstream Performance Mixed Use E3S EC1 CD8P SSD	P69243-K21
HPE 6.4TB NVMe Gen5 Mainstream Performance Mixed Use E3S EC1 CD8P SSD	P69245-K21
HPE 3.2TB NVMe Gen5 High Performance Mixed Use E3S EC1 PS1030 SSD	P70399-K21
HPE 6.4TB NVMe Gen5 High Performance Mixed Use E3S EC1 PS1030 SSD	P70401-K21
HPE 12.8TB NVMe Gen5 High Performance Mixed Use E3S EC1 PS1030 SSD	P70403-K21
HPE 1.6TB NVMe Gen5 Mainstream Performance Mixed Use E3S EC1 EDSFF SPDM PE1030 SSD	P77262-K21
HPE 3.2TB NVMe Gen5 Mainstream Performance Mixed Use E3S EC1 EDSFF SPDM PE1030 SSD	P77265-K21
HPE 6.4TB NVMe Gen5 Mainstream Performance Mixed Use E3S EC1 EDSFF SPDM PE1030 SSD	P77267-K21

SED (Self-Encryption Drive)

HPE 3.2TB NVMe Gen5 High Performance Mixed Use E3S EC1 Self-encrypting FIPS 140-3 CM7 SSD	P70669-K21
HPE 6.4TB NVMe Gen5 High Performance Mixed Use E3S EC1 Self-encrypting FIPS 140-3 CM7 SSD	P70672-K21

Read Intensive – PCIe/NVMe EDSFF - E3S EC1 EDSFF Solid State Drives

HPE 3.84TB NVMe Gen5 High Performance Read Intensive E3S EC1 EDSFF SPDM PM1743 SSD	P57799-K21
HPE 7.68TB NVMe Gen5 High Performance Read Intensive E3S EC1 EDSFF SPDM PM1743 SSD	P57803-K21
HPE 15.36TB NVMe Gen5 High Performance Read Intensive E3S EC1 EDSFF SPDM PM1743 SSD	P57807-K21
HPE 3.84TB NVMe Gen5 High Performance Read Intensive E3S EC1 EDSFF SPDM CM7 SSD	P61179-K21
HPE 7.68TB NVMe Gen5 High Performance Read Intensive E3S EC1 EDSFF SPDM CM7 SSD	P61183-K21
HPE 15.36TB NVMe Gen5 High Performance Read Intensive E3S EC1 EDSFF SPDM CM7 SSD	P61187-K21
HPE 1.92TB NVMe Gen5 Mainstream Performance Read Intensive E3S EC1 CD8P SSD	P69234-K21
HPE 3.84TB NVMe Gen5 Mainstream Performance Read Intensive E3S EC1 CD8P SSD	P69237-K21
HPE 7.68TB NVMe Gen5 Mainstream Performance Read Intensive E3S EC1 CD8P SSD	P69239-K21
HPE 15.36TB NVMe Gen5 Mainstream Performance Read Intensive E3S EC1 CD8P SSD	P69546-K21
HPE 3.84TB NVMe Gen5 High Performance Read Intensive E3S EC1 PS1010 SSD	P70392-K21
HPE 7.68TB NVMe Gen5 High Performance Read Intensive E3S EC1 PS1010 SSD	P70395-K21
HPE 15.36TB NVMe Gen5 High Performance Read Intensive E3S EC1 PS1010 SSD	P70397-K21
HPE 1.92TB NVMe Gen5 Mainstream Performance Read Intensive E3S EC1 EDSFF SPDM PE1010 SSD	P77269-K21
HPE 3.84TB NVMe Gen5 Mainstream Performance Read Intensive E3S EC1 EDSFF SPDM PE1010 SSD	P77271-K21
HPE 7.68TB NVMe Gen5 Mainstream Performance Read Intensive E3S EC1 EDSFF SPDM PE1010 SSD	P77273-K21
HPE 15.36TB NVMe Gen5 Mainstream Performance Read Intensive E3S EC1 EDSFF SPDM PE1010 SSD	P77275-K21

SED (Self-Encryption Drive)

HPE 7.68TB NVMe Gen5 High Performance Read Intensive E3S EC1 Self-encrypting FIPS 140-3 CM7 SSD	P70674-K21
---	------------

Very Read Optimized – PCIe/NVMe EDSFF - E3S EC1 EDSFF Solid State Drives

HPE 3.84TB NVMe Gen4 Mainstream Performance Very Read Optimized E3S EC1 EDSFF P5430 SSD	P63930-K21
HPE 7.68TB NVMe Gen4 Mainstream Performance Very Read Optimized E3S EC1 EDSFF P5430 SSD	P63934-K21
HPE 15.36TB NVMe Gen4 Mainstream Performance Very Read Optimized E3S EC1 EDSFF P5430 SSD	P63938-K21



Core Options

Read Intensive – 24G/12G SAS - SFF - Solid State Drives

Description

SKU

HPE 7.68TB SAS 12G Read Intensive SFF BC Value SAS Multi Vendor SSD	P40509-K21
HPE 3.84TB SAS 12G Read Intensive SFF BC Value SAS Multi Vendor SSD	P40508-K21
HPE 1.92TB SAS 12G Read Intensive SFF BC Value SAS Multi Vendor SSD	P40507-K21
HPE 960GB SAS 12G Read Intensive SFF BC Value SAS Multi Vendor SSD	P40506-K21
HPE 2.4TB SAS 12G Mission Critical 10K SFF BC 3-year Warranty 512e Self-encrypting HDD	P28618-K21
HPE 1.2TB SAS 12G Mission Critical 10K SFF BC 3-year Warranty Self-encrypting FIPS HDD	P28622-K21
HPE 960GB SAS 24G Read Intensive SFF BC Multi Vendor SSD	P49029-K21
HPE 1.92TB SAS 24G Read Intensive SFF BC Multi Vendor SSD	P49031-K21
HPE 3.84TB SAS 24G Read Intensive SFF BC Multi Vendor SSD	P49035-K21
HPE 7.68TB SAS 24G Read Intensive SFF BC Multi Vendor SSD	P49041-K21
HPE 15.36TB SAS 24G Read Intensive SFF BC Multi Vendor SSD	P49045-K21

SED (Self-Encryption Drive)

HPE 3.84TB SAS Read Intensive SFF BC Self-encrypting FIPS 140-2 PM7 SSD	P63875-K21
---	------------

Mixed Use – 24G/12G SAS - SFF - Solid State Drives

HPE 3.84TB SAS 12G Mixed Use SFF BC Value SAS Multi Vendor SSD	P40512-K21
HPE 1.92TB SAS 12G Mixed Use SFF BC Value SAS Multi Vendor SSD	P40511-K21
HPE 960GB SAS 12G Mixed Use SFF BC Value SAS Multi Vendor SSD	P40510-K21
HPE 800GB SAS 24G Mixed Use SFF BC Multi Vendor SSD	P49047-K21
HPE 1.6TB SAS 24G Mixed Use SFF BC Multi Vendor SSD	P49049-K21
HPE 3.2TB SAS 24G Mixed Use SFF BC Multi Vendor SSD	P49053-K21
HPE 6.4TB SAS 24G Mixed Use SFF BC Multi Vendor SSD	P49057-K21

SED (Self-Encryption Drive)

HPE 1.6TB SAS Mixed Use SFF BC Self-encrypting FIPS 140-2 PM7 SSD	P63871-K21
HPE 1.6TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 Self-encrypting FIPS 140-3 CM7 SSD	P61043-K21
HPE 3.2TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 Self-encrypting FIPS 140-3 CM7 SSD	P61051-K21
HPE 6.4TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 Self-encrypting FIPS 140-3 CM7 SSD	P61059-K21

Read Intensive - 6G SATA - SFF - Solid State Drives

HPE 7.68TB SATA 6G Read Intensive SFF BC Multi Vendor SSD	P40501-K21
HPE 3.84TB SATA 6G Read Intensive SFF BC Multi Vendor SSD	P40500-K21
HPE 1.92TB SATA 6G Read Intensive SFF BC Multi Vendor SSD	P40499-K21
HPE 480GB SATA 6G Read Intensive SFF BC Multi Vendor SSD	P40497-K21
HPE 240GB SATA 6G Read Intensive SFF BC Multi Vendor SSD	P40496-K21
HPE 960GB SATA 6G Read Intensive SFF BC Multi Vendor SSD	P40498-K21

SED (Self-Encryption Drive)

HPE 480GB SATA 6G Read Intensive SFF BC Self-encrypting 5400P SSD	P58236-K21
HPE 1.92TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 Self-encrypting FIPS 140-3 CM7 SSD	P61019-K21
HPE 3.84TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 Self-encrypting FIPS 140-3 CM7 SSD	P61027-K21
HPE 7.68TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 Self-encrypting FIPS 140-3 CM7 SSD	P61035-K21



Core Options

Mixed Use - 6G SATA - SFF - Solid State Drives

Description

	SKU
HPE 3.84TB SATA 6G Mixed Use SFF BC Multi Vendor SSD	P40505-K21
HPE 1.92TB SATA 6G Mixed Use SFF BC Multi Vendor SSD	P40504-K21
HPE 960GB SATA 6G Mixed Use SFF BC Multi Vendor SSD	P40503-K21
HPE 480GB SATA 6G Mixed Use SFF BC Multi Vendor SSD	P40502-K21

SED (Self-Encryption Drive)

HPE 960GB SATA 6G Mixed Use SFF BC Self-encrypting 5400M SSD	P58244-K21
--	------------

Read Intensive - 24G SAS - LFF - Solid State Drives

HPE 7.68TB SAS 24G Read Intensive LFF LPC Multi Vendor SSD	P49040-K21
--	------------

Mixed Use - 12G SAS - LFF - Solid State Drives

HPE 960GB SAS 12G Mixed Use LFF LPC Value SAS Multi Vendor SSD	P37009-K21
--	------------

Read Intensive - 6G SATA - LFF - Solid State Drives

HPE 960GB SATA 6G Read Intensive LFF LPC Multi Vendor SSD	P47808-K21
---	------------

Read Intensive - NVMe - SFF - Solid State Drives

HPE 1.92TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 PM1733a SSD	P50216-K21
HPE 3.84TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 PM1733a SSD	P50219-K21
HPE 7.68TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 PM1733a SSD	P50222-K21
HPE 15.36TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 PM1733a SSD	P50224-K21
HPE 15.36TB NVMe Gen4 Mainstream Performance Read Intensive SFF BC U.3 Static SPDM Multi Vendor SSD	P69255-K21
HPE 7.68TB NVMe Gen4 Mainstream Performance Read Intensive SFF BC U.3 Static V2 Multi Vendor SSD	P64848-K21
HPE 3.84TB NVMe Gen4 Mainstream Performance Read Intensive SFF BC U.3 Static V2 Multi Vendor SSD	P64846-K21
HPE 1.92TB NVMe Gen4 Mainstream Performance Read Intensive SFF BC U.3 Static V2 Multi Vendor SSD	P64844-K21
HPE 960GB NVMe Gen4 Mainstream Performance Read Intensive SFF BC U.3 Static V2 Multi Vendor SSD	P64842-K21
HPE 1.92TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 CM7 SSD	P63829-K21
HPE 3.84TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 CM7 SSD	P63833-K21
HPE 7.68TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 CM7 SSD	P63837-K21
HPE 15.36TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 CM7 SSD	P63841-K21
HPE 7.68TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 PS1010 SSD	P70434-K21
HPE 15.36TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 PS1010 SSD	P70436-K21

SED (Self-Encryption Drive)

HPE 1.92TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 Self-encrypting FIPS 140-3 CM7 SSD	P61019-K21
HPE 3.84TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 Self-encrypting FIPS 140-3 CM7 SSD	P61027-K21
HPE 7.68TB NVMe Gen4 High Performance Read Intensive SFF BC U.3 Self-encrypting FIPS 140-3 CM7 SSD	P61035-K21



Core Options

Mixed Use - NVMe - SFF - Solid State Drives

Description	SKU
HPE 1.6TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD	P50227-K21
HPE 3.2TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD	P50230-K21
HPE 6.4TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD	P50233-K21
HPE 1.6TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD	P50227-K21
HPE 3.2TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD	P50230-K21
HPE 6.4TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD	P50233-K21
HPE 6.4TB NVMe Gen4 Mainstream Performance Mixed Use SFF BC U.3 Static V2 Multi Vendor SSD	P65023-K21
HPE 3.2TB NVMe Gen4 Mainstream Performance Mixed Use SFF BC U.3 Static V2 Multi Vendor SSD	P65015-K21
HPE 800GB NVMe Gen4 Mainstream Performance Mixed Use SFF BC U.3 Static V2 Multi Vendor SSD	P64999-K21
HPE 1.6TB NVMe Gen4 Mainstream Performance Mixed Use SFF BC U.3 Static V2 Multi Vendor SSD	P65007-K21
HPE 1.6TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 CM7 SSD	P63845-K21
HPE 3.2TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 CM7 SSD	P63849-K21
HPE 6.4TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 CM7 SSD	P63853-K21
HPE 3.2TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PS1030 SSD	P70426-K21
HPE 6.4TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PS1030 SSD	P70428-K21

HPE Networking

200 Gigabit Ethernet adapters

Description	SKU
-------------	-----

Notes: Not supported if processors equal or greater than 270W

100 Gigabit Ethernet adapters

Mellanox MCX623106AS-CDAT Ethernet 100Gb 2-port QSFP56 Adapter for HPE	P25960-B21
--	------------

Notes: Not supported if processors equal or greater than 270W

Intel E810-CQDA2 Ethernet 100Gb 2-port QSFP28 Adapter for HPE	P21112-B21
---	------------

Notes: Not supported if processors equal or greater than 270W

25 Gigabit Ethernet adapters

Broadcom BCM57504 Ethernet 10/25Gb 4-port SFP28 Adapter for HPE	P26264-B21
---	------------

Broadcom BCM57414 Ethernet 10/25Gb 2-port SFP28 Adapter for HPE	P26262-B21
---	------------

HPE Ethernet 10/25Gb 2-port Secure Network Adapter	S2A69A
--	--------

Intel E810-XXVDA2 Ethernet 10/25Gb 2-port SFP28 Adapter for HPE	P08443-B21
---	------------

Intel E810-XXVDA4 Ethernet 10/25Gb 4-port SFP28 Adapter for HPE	P08458-B21
---	------------

Mellanox MCX631102AS-ADAT Ethernet 10/25Gb 2-port SFP28 Adapter for HPE	P42044-B21
---	------------

10 Gigabit Ethernet adapters

Broadcom BCM57416 Ethernet 10Gb 2-port BASE-T Adapter for HPE	P26253-B21
---	------------

Broadcom BCM57412 Ethernet 10Gb 2-port SFP+ Adapter for HPE	P26259-B21
---	------------

1 Gigabit Ethernet adapters

Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T Adapter for HPE	P51178-B21
---	------------

Intel I350-T4 Ethernet 1Gb 4-port BASE-T Adapter for HPE	P21106-B21
--	------------



Core Options

OCP 3.0 Adapters

Description

	SKU
Intel I350-T4 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE	P08449-B21
Broadcom BCM57416 Ethernet 10Gb 2-port BASE-T OCP3 Adapter for HPE	P10097-B21
Broadcom BCM57414 Ethernet 10/25Gb 2-port SFP28 OCP3 Adapter for HPE	P10115-B21
Intel E810-XXVDA2 Ethernet 10/25Gb 2-port SFP28 OCP3 Adapter for HPE	P10106-B21
Intel E810-CQDA2 Ethernet 100Gb 2-port QSFP28 OCP3 Adapter for HPE	P22767-B21
Broadcom BCM57504 Ethernet 10/25Gb 4-port SFP28 OCP3 Adapter for HPE	P26269-B21
Broadcom BCM57412 Ethernet 10Gb 2-port SFP+ OCP3 Adapter for HPE	P26256-B21
Mellanox MCX631432AS-ADAI Ethernet 10/25Gb 2-port SFP28 OCP3 Adapter for HPE	P42041-B21
Broadcom BCM5719 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE	P51181-B21

Storage Offload Adapters

HPE NV60100M 100Gb 2-port Storage Offload Adapter	R8M41A
---	--------

HPE InfiniBand

Notes: Recommended system Ambient temperature: 25C.

Description

	SKU
HPE InfiniBand NDR 1-port OSFP PCIe5 x16 MCX75310AAS-NEAT Adapter	P45641-B21
HPE InfiniBand NDR/Ethernet 400Gb 1-port OSFP PCIe5 x16 MCX75310AAS-NEAT Adapter	P45641-B23
HPE InfiniBand NDR200/Ethernet 200Gb 1-port OSFP PCIe5 x16 MCX75310AAS-HEAT Adapter	P45642-B22
HPE InfiniBand NDR200/Ethernet 200GbE 2-port QSFP112 PCIe5 x16 MCX755106AC-HEAT Adapter	P65333-B21
HPE InfiniBand HDR/Ethernet 200Gb 1-port QSFP56 PCIe4 x16 MCX653105A-HDAT Adapter	P23664-B21
Notes: Not supported if processors equal or greater than 270W	
HPE InfiniBand HDR/Ethernet 200Gb 2-port QSFP56 PCIe4 x16 MCX653106A-HDAT Adapter	P31324-B21
Notes: Not supported if processors equal or greater than 270W	
HPE InfiniBand HDR100/Ethernet 100Gb 1-port QSFP56 PCIe4 x16 MCX653105A-ECAT Adapter	P23665-B21
Notes: Not supported if processors equal or greater than 270W	
HPE InfiniBand HDR100/Ethernet 100Gb 2-port QSFP56 PCIe4 x16 MCX653106A-ECAT Adapter	P23666-B21
Notes: Not supported if processors equal or greater than 270W	
HPE InfiniBand HDR/Ethernet 200Gb 2-port QSFP56 PCIe4 x16 OCP3 MCX653436A-HDAI Adapter	P31348-B21

Notes:

- HPE OCP Thermal Enhancement Kit (P28727-B21) is required.
- For additional InfiniBand information:
<https://www.hpe.com/h20195/v2/GetHTML.aspx?docname=c04154440>.



Core Options

HPE Power Supplies

HPE Flexible Slot (Flex Slot) Power Supplies share a common electrical and physical design that allows for hot plug, tool-less installation into HPE ProLiant Gen10 Performance Servers. Flex Slot power supplies are certified for high-efficiency operation and offer multiple power output options, allowing users to "right-size" a power supply for specific server configurations. This flexibility helps to reduce power waste, lower overall energy costs, and avoid "trapped" power capacity in the data center.

All pre-configured servers ship with a standard 6-foot IEC C-13/C-14 jumper cord (A0K02A). This jumper cord is also included with each standard AC power supply option kit. If a different power cord is required, please check the [ProLiant Power Cables](#) web page.

To review the power requirements for your selected system, please use the [HPE Power Advisor Tool](#).

For information on power specifications and technical content visit [HPE Server power supplies](#)

HPE Flex Slot Platinum Hot-plug Power supplies

Description	SKU
HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	P38995-B21
HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit	P03178-B21
HPE 1600W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	P38997-B21
Notes: Only supports high line voltage (200 VAC to 240 VAC).	
HPE 1800W-2200W Flex Slot Titanium Hot Plug Power Supply Kit	P44712-B21
Notes: Only supports high line voltage (200 VAC to 240 VAC).	
HPE 1600W Flex Slot -48VDC Hot Plug Power Supply Kit	P17023-B21



Additional Options

HPE Greenlake for Compute Ops Management

Notes: HPE Greenlake for Compute Ops Management for cloud-native management is available in two tiers: Standard, for managing systems individually, or Enhanced for management of multiple systems. Billing frequency is available as upfront, monthly, quarterly, or annual payments.

Description	SKU
HPE Compute Ops Management Enhanced 1-year Upfront Alletra 4000 SaaS	S1E11AAE
HPE Compute Ops Management Enhanced 3-year Upfront Alletra 4000 SaaS	S1E12AAE
HPE Compute Ops Management Enhanced 5-year Upfront Alletra 4000 SaaS	S1E13AAE

Embedded Management

Notes: Some options may not be integrated at the factory. To ensure only valid configurations are ordered, Hewlett Packard Enterprise recommends the use of an HPE approved configurator. Contact your local sales representative for additional information.

HPE iLO Advanced

HPE iLO Advanced 1-server License with 1yr Support on iLO Licensed Features	512485-B21
HPE iLO Advanced AKA Tracking License with 1yr Support on iLO Licensed Features	512487-B21
HPE iLO Advanced 1-server License with 3yr Support on iLO Licensed Features	BD505A
HPE iLO Advanced AKA Tracking License with 3yr Support on iLO Licensed Features	BD507A
HPE iLO Advanced Electronic License with 1yr Support on iLO Licensed Features	E6U59ABE
HPE iLO Advanced Electronic License with 3yr Support on iLO Licensed Features	E6U64ABE

HPE iLO Common Password

HPE iLO Common Password FIO Setting	P08040-B21
-------------------------------------	------------

Notes:

- Replaces iLO default randomized password by an HPE defined common password. HPE highly recommends changing this password immediately after the initial onboarding process.
- Customers who want to choose their own custom iLO default password should use the HPE Factory Express Integration Services.

HPE Converged Infrastructure Management Software

HPE OneView Advanced (with HPE iLO Advanced)

Description	SKU
HPE OneView including 3yr 24x7 Support Physical 1-server LTU	E5Y34A
HPE OneView including 3yr 24x7 Support Flexible Quantity E-LTU	E5Y35AAE

HPE OneView Advanced (without HPE iLO Advanced)

HPE OneView w/o iLO including 3yr 24x7 Support 1-server LTU	P8B24A
HPE OneView w/o iLO including 3yr 24x7 Support Track 1-server LTU	P8B25A
HPE OneView w/o iLO including 3yr 24x7 Support Flexible Quantity E-LTU	P8B26AAE

Notes:

- Licenses ship without media. The HPE OneView Media Kit can be ordered separately, or can be downloaded at: <https://www.hpe.com/us/en/integrated-systems/software.html>.
- Electronic and Flexible-Quantity licenses can be used to purchase multiple licenses with a single activation key.
- Licenses ship without media. The HPE OneView Media Kit can be ordered separately, or can be downloaded at: <https://www.hpe.com/us/en/integrated-systems/software.html>.



Additional Options

HPE Security

Description	SKU
HPE Gen11 2U Storage Bezel Kit	P51688-B21
HPE Bezel Lock Kit	875519-B21

HPE Smart Array Controllers

Notes:

- MR (MegaRAID) series controllers are not supported with Intelligent Provisioning feature
- For more information on the HPE Gen11 Storage Controller, please refer to:
 - [HPE Compute MR Gen11 Controllers Quick Spec](#)
 - [HPE Compute SR Gen11 Controllers Quick Spec](#)

Essential RAID Controllers

Description	SKU
HPE Smart Array E208e-p SR Gen10 (8 External Lanes/No Cache) 12G SAS PCIe Plug-in Controller	804398-B21

Notes: For more information on the HPE Smart Array E208i-p SR Gen10 Controller, please refer to the [QuickSpecs](#)

HPE Tri-Mode Controllers

HPE SR932i-p Gen11 x32 Lanes 8GB Wide Cache PCI SPDM Plug-in Storage Controller	P47184-B21
HPE MR416i-p Gen11 x16 Lanes 8GB Cache PCI SPDM Plug-in Storage Controller	P47777-B21
HPE MR216i-p Gen11 x16 Lanes without Cache PCI SPDM Plug-in Storage Controller	P47785-B21

HPE Smart Storage Battery

HPE 96W Smart Storage Lithium-ion Battery with 145mm Cable Kit	P01366-B21
--	------------

Notes: Required when more than two controllers are selected.

HPE Smart Storage Hybrid Capacitor with 145mm Cable Kit	P02377-B21
---	------------

HPE NVMe OS Boot Device

HPE NS204i-u Gen11 NVMe Hot Plug Boot Optimized Storage Device	P48183-B21
--	------------

Optional Software

Description	SKU
HPE Smart Array SR Secure Encryption (Data at Rest Encryption/per Server Entitlement) E-LTU	Q2F26AAE

Software RAID

Description	SKU
Intel Virtual RAID on CPU Premium FIO Software for HPE	R7J57A

Notes:

- The Intel® VROC Premium is available for RAID support 0, 1, 5, 10 at the field.
- If Intel® VROC Premium is the primary controller, then the following RAID levels are allowed: 0, 1, 5 (available from RAID FIO settings at HPE factory). Requires selection of NVMe Drives through Direct Attach supported only.
- If Intel® RAID is being selected in a configuration with VROC and internal controller, then Customer Defined RAID Setting (389692-B21) must be selected.



Additional Options

Description

Intel Virtual RAID on CPU Premium E-RTU for HPE

SKU
R7J59AAE

Notes: Same as Intel Virtual RAID on CPU Premium FIO Software for HPE (R7J57A), but intended for field deployments.

Notes:

- Intel® VROC Standard
- The Intel® VROC Standard is available for RAID support 0, 1, 5 at the field. If Intel® VROC Standard is the primary controller, then only following RAID levels are allowed: 0, 1 (available from RAID FIO settings at HPE factory). Requires selection of NVMe Drives through Direct Attach Supported only.
- If Intel® RAID is being selected in a configuration with VROC and internal controller, then Customer Defined RAID Setting (389692-B21) must be selected.

Intel Virtual RAID on CPU Standard E-RTU for HPE

SOE38AAE

Notes: Same as Intel Virtual RAID on CPU Standard FIO Software for HPE (SOE37A), but intended for field deployments.

GPGPU

Notes:

- There is no Energy Star 3.0 certification with Graphic cards.
- Please contact your HPE representative for the system thermal details

Description

NVIDIA A2 16GB PCIe Non-CEC Accelerator for HPE

SKU
R9H23C

Notes: PCIe 4.0

NVIDIA L4 24GB PCIe Accelerator for HPE

S0K89C

HPE Storage Options

Emulex Fibre Channel HBAs

Description

HPE SN1200E 16Gb Single Port Fibre Channel Host Bus Adapter

Q0L13A

HPE SN1200E 16Gb Dual Port Fibre Channel Host Bus Adapter

Q0L14A

HPE SN1610E 32Gb 1-port Fibre Channel Host Bus Adapter

R2J62A

HPE SN1610E 32Gb 2-port Fibre Channel Host Bus Adapter

R2J63A

HPE SN1700E 64Gb 1-port Fibre Channel Host Bus Adapter

R7N77A

HPE SN1700E 64Gb 2-port Fibre Channel Host Bus Adapter

R7N78A

QLogic Fibre Channel HBAs

HPE SN1100Q 16Gb Single Port Fibre Channel Host Bus Adapter

P9D93A

HPE SN1100Q 16Gb Dual Port Fibre Channel Host Bus Adapter

P9D94A

HPE SN1610Q 32Gb 1-port Fibre Channel Host Bus Adapter

R2E08A

HPE SN1610Q 32Gb 2-port Fibre Channel Host Bus Adapter

R2E09A

HPE SN1700Q 64Gb 1-port Fibre Channel Host Bus Adapter

R7N86A

HPE SN1700Q 64Gb 2-port Fibre Channel Host Bus Adapter

R7N87A



Additional Options

HPE Racking Options

Rail Kits

Description

	SKU
HPE 2U Shelf-Mount Adjustable Rail Kit	822731-B21
HPE Apollo 4200 Gen9 FIO Strap Shipping Bracket	822640-B21

Notes: This SKU is used for shipping servers that are integrated in a rack.

HPE Optical Drives

Description

	SKU
HPE Mobile USB DVD-RW Optical Drive	701498-B21

Notes: This is only supported on USB 3.0 ports.

HPE Racks

- Please see the [HPE Advanced Series Racks QuickSpecs](#) for information on additional racks options and rack specifications.
- Please see the [HPE Enterprise Series Racks QuickSpecs](#) for information on additional racks options and rack specifications.
- Please see the [HPE Standard Series Racks QuickSpecs](#) for information on additional racks options and rack specifications.

HPE Power Distribution Units (PDUs)

- Please see the [HPE Basic Power Distribution Units \(PDU\) QuickSpecs](#) for information on these products and their specifications.
- Please see the [HPE Metered Power Distribution Units \(PDU\) QuickSpecs](#) for information on these products and their specifications.
- Please see the [HPE Intelligent Power Distribution Unit \(PDU\) QuickSpecs](#) for information on these products and their specifications.
- Please see the [HPE Metered and Switched Power Distribution Units \(PDU\) QuickSpecs](#) for information on these products and their specifications.

HPE Uninterruptible Power Systems (UPS)

To learn more, please visit the [HPE Uninterruptible Power Systems \(UPS\) web page](#).

- Please see the [HPE DirectFlow Three Phase Uninterruptible Power System QuickSpecs](#) for information on these products and their specifications.
- Please see the [HPE Line Interactive Single Phase UPS QuickSpecs](#) for information on these products and their specifications.

HPE USB and SD Options

HPE Enterprise Mainstream Flash Media Kits for Memory Cards

Description

	SKU
HPE 32GB microSD RAID 1 USB Boot Drive	P21868-B21



Technical Specifications

System Unit	
Dimensions (Height x Width x Depth)	87.5 x 448.0 x 812.80 mm 3.44 x 17.63 x 32.00 in
Weight (approximate)	
Minimum	21.28 kg 46.91 lb
Maximum.	42.84 kg 94.45 lb
Input Requirements (per power supply)	
Rated Line Voltage	100 to 120 VAC 200 to 240 VAC
BTU Rating	
Maximum	For 800W Power Supply: 3207 BTU/hr (at 100 VAC), 3071 BTU/hr (at 200 VAC), 3112 BTU/hr (at 240 VAC) for China Only
Power Supply Output (per power supply)	
Rated Steady-State Power	For 1600W Power Supply: 1600W (at 240 VAC), 1600W (at 240 VDC) for China only For 800W Power Supply: 800W (at 100 VAC), 800W (at 240 VAC), 800W (at 240 VDC) input for China only
Maximum Peak Power	For 1600W Power Supply: 1600W (at 200 to 240 1VAC), 1600W (at 240 VDC) input for China only
System Inlet Temperature	
Standard Operating Support	<p>10° to 35°C (50° to 95°F) at sea level with an altitude derating of 1.0°C per every 305 m (1.8°F per every 1000 ft) above sea level to a maximum of 3050 m (10,000 ft), no direct sustained sunlight. Maximum rate of change is 20°C/hr (36°F/hr). The upper limit and rate of change may be limited by the type and number of options installed.</p> <p>System performance during standard operating support may be reduced if operating with a fan fault or above 30°C (86°F).</p> <p>For approved hardware configurations, the supported system inlet range is extended to be: 5° to 10°C (41° to 50°F) and 35° to 40°C (95° to 104°F) at sea level with an altitude derating of 1.0°C per every 175 m (1.8°F per every 574 ft) above 900 m (2953 ft) to a maximum of 3050 m (10,000 ft). The approved hardware configurations for this system are listed at the URL: http://www.hpe.com/servers/ashrae</p>
Extended Ambient Operating Support	<p>For approved hardware configurations, the supported system inlet range is extended to be: 40° to 45°C (104° to 113°F) at sea level with an altitude derating of 1.0°C per every 125 m (1.8°F per every 410 ft) above 900 m (2953 ft) to a maximum of 3050 m (10,000 ft). The approved hardware configurations for this system are listed at the URL: http://www.hpe.com/servers/ashrae</p> <p>System performance may be reduced if operating in the extended ambient operating range or with a fan fault.</p>

Technical Specifications

Relative Humidity (non-condensing)

Operating	8% to 90% - Relative humidity (Rh), 28°C maximum wet bulb temperature, non-condensing.
Non-operating	5 to 95% relative humidity (Rh), 38.7°C (101.7°F) maximum wet bulb temperature, non-condensing.

Altitude

Operating	3050 m (10,000 ft). This value may be limited by the type and number of options installed. Maximum allowable altitude change rate is 457 m/min (1500 ft/min).
Non-operating	9144 m (30,000 ft). Maximum allowable altitude change rate is 457 m/min (1500 ft/min).

Acoustic Noise

Listed are the declared A-Weighted sound power levels (LWAd) and declared average bystander position A-Weighted sound pressure levels (LpAm) when the product is operating in a 23°C ambient environment. Noise emissions were measured in accordance with ISO 7779 (ECMA 74) and declared in accordance with ISO 9296 (ECMA 109). The listed sound levels apply to standard shipping configurations. Additional options may result in increased sound levels. Please have your HPE representative provide information from the HPE EMESC website for further technical details regarding the configurations listed below.

Configuration SKU	Entry	Base	Performance
Idle			
LWAd	5.9 B	6.4 B	5.4 B
LpAm	35 dBA	35 dBA	36 dBA
Operating			
LWAd	6.0 B	7.1 B	6.3 B
LpAm	36 dBA	38 dBA	45 dBA

Notes: Acoustics levels presented here are generated by the test configuration only. Acoustics levels will vary depending on system configuration. Values are subject to change without notification and are for reference only

Emissions Classification (EMC)

To view the regulatory information for your product, view the Safety and Compliance Information for Server, Storage, Power, Networking, and Rack Products, available at the Hewlett Packard Enterprise Support Center:

<http://www.hpe.com/support/Safety-Compliance-EnterpriseProducts>

Environment-friendly Products and Approach - End-of-life Management and Recycling

Hewlett Packard Enterprise offers **end-of-life product return, trade-in, and recycling programs**, in many geographic areas, for our products. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the **Hewlett Packard Enterprise web site**. These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment.

TCO Certified

The HPE Alletra Storage Server 4120 has been TCO Certified. All HPE TCO Certified products can be found on **TCO Certified Product Finder**. More information on TCO Certified can be downloaded here:

<https://www.hpe.com/us/en/about/environment/eco-labels.html>



Summary of Changes

Date	Version History	Action	Description of Change
03-Feb-2025	Version 22	Changed	Core Options section was updated Obsolete SKUs removed - 5 SKUs
06-Jan-2025	Version 21	Changed	Core Options and Additional Options sections were updated Obsolete SKUs removed - 10 SKUs
04-Nov-2024	Version 20	Changed	Obsolete SKUs removed - P56585-K21
07-Oct-2024	Version 19	Changed	Configuration Information and Core Options sections were updated
03-Sep-2024	Version 18	Changed	Standard Features, Configuration Information and Core Options sections were updated
15-Jul-2024	Version 17	Changed	Configuration Information and Core Options sections were updated
01-Jul-2024	Version 16	Changed	Core Options section was updated
03-Jun-2024	Version 15	Changed	Core Options section was updated
06-May-2024	Version 14	Changed	Configuration Information, Core Options, and Additional Options sections were updated
04-Mar-2024	Version 13	Changed	Core Options section was updated
05-Feb-2024	Version 12	Changed	Configuration Information and Core Options sections were updated
08-Jan-2024	Version 11	Changed	Standard Features, Configuration Information and Core Options sections were updated
14-Dec-2023	Version 10	Changed	Overview, Standard Features, Configuration Information, Core Options, and Additional Options sections were updated HPE Services Rebranding
06-Nov-2023	Version 9	Changed	Overview, Standard Features, Configuration Information, Core Options, Additional Options and Technical Specifications sections were updated
05-Sep-2023	Version 8	Changed	Core Options section was updated
07-Aug-2023	Version 7	Changed	Standard Features, Configuration Information and Core Options sections were updated
10-Jul-2023	Version 6	Changed	Standard Features and Configuration Information sections were updated
05-Jun-2023	Version 5	Changed	Standard Features and Configuration Information sections were updated
03-Apr-2023	Version 4	Changed	Overview, Standard Features, Configuration Information, Core Options and Technical Specifications sections were updated
06-Mar-2023	Version 3	Changed	Configuration Information and Core Options sections were updated Add SKU – P44712-B21
06-Feb-2023	Version 2	Changed	Additional Options section was updated Add SKUs – R7N86A and R7N87A
10-Jan-2023	Version 1	New	New QuickSpecs



Copyright

Make the right purchase decision.
Contact our presales specialists.



© Copyright 2025 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Intel® and Xeon® are registered trademarks of Intel Corporation in the U.S. and other countries. Microsoft®, Windows®, and Windows Server® are U.S. registered trademarks of the Microsoft group of companies.

For hard drives, 1GB = 1 billion bytes. Actual formatted capacity is less

a50006973enw - 17083 - Worldwide - V22 - 03-February-2025